NITROGEN - nitrogen gas
American Welding & Gas

NITROGEN,
COMPRESSED
UN1066
7727-37-9
NITROGEN, NF
Pressure: _____ PSIG at 70°F
Size: _____
Contents: _____ Liters
DO NOT REMOVE THIS PRODUCT LABEL.
Rx Only. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced the use and frequency and duration of administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken.
CAUTION: HIGH PRESSURE GAS. CAN CAUSE RAPID SUFFOCATION. Store and use with adequate ventilation. Use equipment rated for cylinder pressure. Use a back flow preventive device in the piping. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS).
FIRST AID:
IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
TO BE REFILLED BY AN INWELD AUTHORIZED FACILITY ONLY. RETURN WITH 25

PSIG
REFRIGERATED LIQUID
NITROGEN, REFRIGERATED LIQUID NF

UN1977
ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
Rx only
WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.
WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE.
CAN CAUSE RAPID SUFFOCATION.
CAN CAUSE SEVER FROSTBITE.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container movement.
Cylinder temperature should not exceed 52C (125F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with the Material Safety Data Sheet (MSDS).
FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
IN CASE OF FROSTBITE, obtain medical treatment immediately.
CAS: 7727-37-9
DO NOT REMOVE THIS PRODUCT LABEL.
AMERICAN WELDING and GAS
WILLMAR, MN 56201

REFRIGERATED LIQUI

NITROGEN, REFRIGERATED LIQUID NF

UN1977

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

℞ only

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indicat effects, dosages, methods, and frequency and duration o administration, and with the hazards, contraindications a side effects and the precautions to be taken.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE
CAN CAUSE RAPID SUFFOCATION.
CAN CAUSE SEVERE FROSTBITE.

Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container movem
Cylinder temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with the **Material Safety Data Sheet (MSD**

FIRST AID: **IF INHALED**, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxyg Call a physician.

IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.

AMERICAN WELDING & GAS