

OXYGEN- oxygen gas
ADF Welding & Medical, Inc.

Oxygen

Oxygen Shoulder Label


OXYGEN, COMPRESSED USP UN 1072 OXYGEN 2 (R-K14A)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS: LTRS __ CU.FT. __

ADF WELDING & MEDICAL, INC.

312 DODD BOULEVARD SE • ROME, GA 30161 • 706-295-5772





Oxygen Body Label

ADF WELDING & MEDICAL, INC

312 Dodd Blvd. S.E. Rome, GA 30161

706-295-5772

OXYGEN, COMPRESSED UN 1072

DO NOT REMOVE THIS LABEL

Pressure: PSIG at 70°F

Size

Contents: Liters

OXYGEN2

OXYGEN* U.S.P.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. User shall secure cylinder in use and in storage. Use in upright position. Close valve after each use. Keep valve protective cap in place when not in use, if so equipped. Use in accordance of MSDS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications.

CAUTION: Federal law prohibits dispensing without a prescription, Rx only.

WARNING: Uninterrupted use of high concentration of oxygen for more than 5 hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless in conjunction with resuscitative equipment. Keep Out of Reach of Children. Do not use or store near heat or open flame. CAS 7782-44-7 *PRODUCED BY AIR LIQUEFACTION RETURN WITH 25 PSIG

ADF WELDING & MEDICAL, INC.

312 Dodd Blvd. S. E. Rome, GA 30161

706-295-5772

OXYGEN, COMPRESSED

UN 1072

DO NOT REMOVE THIS LABEL

Pressure: PSIG at 70° F,
Size
Contents liters



OXYGEN* U.S.P.

WARNING: HIGH PRESSURE OXIDIZING GAS.
VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. User shall secure cylinder in use and in storage. Use in upright position. Close valve after each use. Keep valve protective cap in place when not in use. If so equipped. Use in accordance with MSDS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications,

CAUTION: Federal law prohibits dispensing without a prescription only.

WARNING: Uninterrupted use of high concentrations of oxygen for more than 5 hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep Out of Reach of Children. Do not use or store near heat or open flame.
CAS 7782-44-7 *PRODUCED BY AIR LIQUEFACTION RETURN WITH 25 PSIG.

ADF WELDING & MEDICAL, INC.

312 Dodd Blvd. S. E. Rome, GA 30161

706-295-5772

OXYGEN, COMPRESSED

UN 1072

DO NOT REMOVE THIS LABEL

Pressure: PSIG at 70° F,
Size
Contents liters



OXYGEN* U.S.P.

WARNING: HIGH PRESSURE OXIDIZING GAS.
VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. User shall secure cylinder in use and in storage. Use in upright position. Close valve after each use. Keep valve protective cap in place when not in use. If so equipped. Use in accordance with MSDS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications,

CAUTION: Federal law prohibits dispensing without a prescription only.

WARNING: Uninterrupted use of high concentrations of oxygen for more than 5 hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep Out of Reach of Children. Do not use or store near heat or open flame.
CAS 7782-44-7 *PRODUCED BY AIR LIQUEFACTION RETURN WITH 25 PSIG.

Oxygen Refrigerated

OXYGEN

REFRIGERATED LIQUID, U.S.P.

UN 1073

(CRYOGENIC LIQUID) Produced by Air Liquefaction

OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING

EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications

RX only.

WARNING! Uninterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Use in accordance with Material Safety Data Sheet.

WARNING: Caution Federal Law Prohibits Dispensing without Prescription

FIRST AID

IN CASE OF FROSTBITE, obtain medical treatment immediately.

PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.

DO NOT REMOVE THIS PRODUCT LABEL

OXYGEN
REFRIGERATED LIQUID, U.S.P.
UN 1073
(CRYOGENIC LIQUID) Produced by Air Liquefaction



ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

WARNING!
EXTREMELY COLD OXIDIZING
LIQUID AND GAS UNDER
PRESSURE.
VIGOROUSLY ACCELERATES
COMBUSTION. COMBUSTIBLES
IN CONTACT WITH LIQUID
OXYGEN MAY EXPLODE ON
IGNITION OR IMPACT. CAN
CAUSE SEVERE FROSTBITE.

For emergency use only when
administered by properly trained
personnel for oxygen deficiency
and resuscitation. For all other
medical applications, RX only.

WARNING: Caution Federal Law Prohibits Dispensing without Prescription.

WARNING!
Uninterrupted use of high concentrations
of oxygen over long duration, without
monitoring its effect on oxygen content
of arterial blood, may be harmful. Use only
with pressure reducing equipment and
apparatus designed for oxygen. Do not
attempt to use on patients who have stop-
ped breathing, unless used in conjunction
with resuscitative equipment. Keep oil,
grease, and combustibles away. Use
only with equipment cleaned for oxygen
service. Store and use with adequate
ventilation. Do not get liquid in eyes, on
skin or clothing. For liquid withdrawal,
wear face shield and gloves. Do not drop.
Use hand truck for container movement.
Avoid spills. Do not walk on or roll equip-
ment over spills. Close valve after each
use and when empty. Use in accordance
with Material Safety Data Sheet.

FIRST AID

IN CASE OF FROSTBITE, obtain medical
treatment immediately.

**PLEASE REFER TO THE MATERIAL
SAFETY DATA SHEET FOR
SAFETY AND PRODUCT INFORMATION.**

Company Name:

Lot Number:

Contents:

Expiration Date:



DO NOT REMOVE THIS PRODUCT LABEL

PRINTED BY BATHURST MILLS, INC. 1000 1000 1000

OXYGEN

REFRIGERATED LIQUID, U.S.P.
UN 1073
(CRYOGENIC LIQUID)

Produced by Air Liquefaction



ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

WARNING! EXTREMELY COLD CHOKING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX only.

WARNING: Caution Federal Law Prohibits Dispensing without Prescription.

FIRST AID

IN CASE OF FROSTBITE, obtain medical treatment immediately.

PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.

Company Name: _____

Lot Number: _____

Contents: _____

Expiration Date: _____

FIRST AID

DO NOT REMOVE THIS PRODUCT LABEL

PRINTED BY WATERBURY WFO INC. 303-833-0344

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:64922-233
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:64922-233-01	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
2	NDC:64922-233-02	256 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	

3	NDC:64922-233-03	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
4	NDC:64922-233-04	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
5	NDC:64922-233-05	1698 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
6	NDC:64922-233-06	2549 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
7	NDC:64922-233-08	3450 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
8	NDC:64922-233-09	6900 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
9	NDC:64922-233-10	160 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1990	
10	NDC:64922-233-11	180 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1990	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1990	

Labeler - ADF Welding & Medical, Inc. (609900782)

Registrant - ADF Welding & Medical, Inc. (609900782)

Establishment

Name	Address	ID/FEI	Business Operations
ADF Welding & Medical, Inc.		609900782	manufacture(64922-233)

Revised: 10/2023

ADF Welding & Medical, Inc.