OXYGEN- oxygen gas Machine & Welding Supply Company dba Arc3 Gases South

Oxygen

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. PRODUCED BY AIR LIQUIFACTION

DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

PSIG @ 70 degrees F. Size: Liters:

ARC3 GASES 1636 Hwy 301 South . Dunn, NC 28334 844-534-8021



OXYGEN, REFRIGERATED LIQUID USP UN1073 ARC3 GASES OXYGEN 2 1636 Hwy 301 South . Dunn, NC 28334 844-534-8021 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS;

MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. DO NOT REMOVE THIS PRODUCT LABEL. CAS: 7782-44-7




OXYGEN, COMPRESSED USP UN1072 OXYGEN 2 Content LTRS. CU.FT

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. PRODUCED BY AIR LIQUIFACTION

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the

Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL ARC3 GASES 1636 Hwy 301 South Dunn, NC 28334 844-534-8021



MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL.



OXYGEN, COMPRESSED USP

UN1072

B 141 2015

Size Liters PSIG at 70 F

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL.

ARC3 GASES

1636 Hwy 301 South

Dunn, NC 28334

884-534-8021



WARNING: For emergency use only when administered by properly trained personnel for oxygen decisiency and resuscitation. For all other medical applications, Rx enty. Uninterrupted use o high concentrations of oxygen over a long duration, without enumointoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE: OXIDER, CONTAINS GAS LINDER PRESSURE: MAY EXPLODE IF HEATED. Do not handle until all safety precations have been read and understood. Keep and store away from clothing and other combustible materials. Require valves and ittings free from grease and oil. Use and store only cluber preventive divice in the priping. Use only with equipment of compatible materials of service. Does valve shows the priping. Use only with equipment cleared for oxygen preventive divice in cylinder pressure. Use only with equipment cleared for oxygen preventive divice in Close valve after each use and when empty. Protect from subight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL. DES HWY 301 South Dem, NC 32344 844-534-8021

OXYGEN, COMPRESSED USP UN1072 D 420 2015

Size Liters PSIG at 70 F

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL.

ARC3 GASES

1636 Hwy 301 South

Dunn, NC 28334

884-534-8021



WARNING: For emergency use only when administence by property trained persionine tororygen deficiency, and resuscitation. For all other medical applications, Re-each, Unintrarupted use of high concentrations of oxygen over a long diratilox, without monitoring its effect on oxygen content of arterial block, may be harmul. Do not attempt to use an patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Ligaterialian.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DAMOBE: MAY CAUSE ON INTERSITY FIRE: CONCER, CONTANIS GAS UNDER PRESSURE WY CPPLODE If HATERIDE. Do not handwai writii al asthy prouduros have been read and understood. Keep and store away from clebihog and other combustible materials. Kee yeaks and filtings free from grease and out. Use and store or you dondorn or in a well-weitland place. In case of fire: Stop leak if asts to do so. Use a back flow preventive divide in the placing. Use only with equipment deaned for corgen service. They review to divide (Giose who staff ac actue and whole many): Protect from suithigt whon ambient temperture scoreds \$2° (12°T); Read and follow the Safety Data Sheet (SDS) before use. CAS. NO. 7752-44-7



OXYGEN, COMPRESSED USP

UN1072

E 690 2015

Size Liters PSIG at 70 F

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL.

ARC3 GASES

1636 Hwy 301 South

Dunn, NC 28334

884-534-8021



Cosmitto Act. DMRGRF: MAY ACUSE OR INTENSIFY FIRE: OXIDER: CONTAINS GAS UNDER PRESSURE: MAY CXPLODE IF HEATED. Do not handle until all advety precautions have been read and understool. Keep and store away from collaring and other commutatile materials. Keep valves and fittings fires from grease and oil. Use and abore only outdoors or in a well-vestliad place. It cases of fires: Sogi kaik faite to do so. Use abore. Khow preventive dericks in the placing. Use only with equipment of compatible materials of construction and rated for cyclinder pressure. Use only with equipment cleaned for oxygone service. Open valves slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperatree accesses 25° (1257). Read and follow the Safety Data Sheet (SDS) before use. C.A.S. NO. 7782-44-7



0)	KYGEN						
оху	/gen gas						
Product Information							
Pr	oduct Type		HUMAN PRESCRIPTION DRUG	ltem	Code (Source)		NDC:49575-001
Route of Administration		stration	RESPIRATORY (INHALATION)				
Active Ingredient/Active Moiety							
Ingredient Name Basis of Strength Strength						Strength	
OXYGEN (UNII: S88TT14065) (OXYGE			GEN - UNII:S88TT14065)	OXY	OXYGEN		992 mL in 1 L
Packaging							
#	ltem Code	Pa	ackage Description	M	arketing Start Date	Μ	larketing End Date
1	NDC:49575- 001-01	103 L in 1 CYL Product	INDER; Type 0: Not a Combination	06/	15/1999		
2	NDC:49575- 001-02	126 L in 1 CYL Product	INDER; Type 0: Not a Combination	06/	15/1999		
7	NDC:49575-	150 L in 1 CYL	INDER; Type 0: Not a Combination	061	1 5 /1 0 0 0		

3	001-03	Product	00/13/2888
4	NDC:49575-	198 L in 1 CYLINDER; Type 0: Not a Combination	06/15/1999
-	001-04 NDC:49575-	Product 226 L in 1 CYLINDER; Type 0: Not a Combination	
5	001-05	Product	06/15/1999
6	NDC:49575- 001-06	420 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
7	NDC:49575- 001-07	588 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
8	NDC:49575- 001-08	690 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
9	NDC:49575- 001-09	1133 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
10	NDC:49575- 001-10	1567 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
11	NDC:49575- 001-11	2549 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
12	NDC:49575- 001-12	3160 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
13	NDC:49575- 001-13	3172 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
14	NDC:49575- 001-14	6270 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
15	NDC:49575- 001-15	8510 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
16	NDC:49575- 001-16	127100 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
17	NDC:49575- 001-17	141500 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
18	NDC:49575- 001-18	179803 L in 1 CAN; Type 0: Not a Combination Product	06/15/1999
19	NDC:49575- 001-19	206472 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
20	NDC:49575- 001-20	16750 L in 1 DEWAR; Type 0: Not a Combination Product	06/15/1999
21	NDC:49575- 001-21	24950 L in 1 DEWAR; Type 0: Not a Combination Product	06/15/1999
22	NDC:49575- 001-22	25650 L in 1 DEWAR; Type 0: Not a Combination Product	06/15/1999
23	NDC:49575- 001-23	29069 L in 1 DEWAR; Type 0: Not a Combination Product	06/15/1999
24	NDC:49575- 001-24	33500 L in 1 DEWAR; Type 0: Not a Combination Product	06/15/1999
25	NDC:49575- 001-25	33620 L in 1 DEWAR; Type 0: Not a Combination Product	06/15/1999
26	NDC:49575- 001-26	37619 L in 1 DEWAR; Type 0: Not a Combination Product	06/15/1999
27	NDC:49575- 001-27	7760 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
28	NDC:49575- 001-28	2165 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
29	NDC:49575- 001-29	3137.5 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999
30	NDC:49575- 001-30	3841 L in 1 CYLINDER; Type 0: Not a Combination Product	06/15/1999

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	06/15/1999	

Labeler - Machine & Welding Supply Company dba Arc3 Gases South (065300535)

Establishment					
Name	Address	ID/FEI	Business Operations		
Machine & Welding Supply Company dba Arc3 Gases South		043975085	manufacture(49575-001)		
Establishment					
Name	Address	ID/FEI	Business Operations		
Machine & Welding Supply Company dba Arc3 Gases South		065300535	manufacture(49575-001)		
Establishment					

Name	Address	ID/FEI	Business Operations
Machine & Welding Supply Company dba Arc3 Gases South		962288192	manufacture(49575-001)

Revised: 12/2023

Machine & Welding Supply Company dba Arc3 Gases South