

**OXYGEN- oxygen gas**  
**County Welding Supply Co.**

-----  
**oxygen**

OXYGEN, COMPRESSED USP UN1072  
PRODUCED BY AIR LIQUEFACTION OXYGEN 2


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

COUNTY WELDING SUPPLY COMPANY 69 E. DEWEY AVE. . WHARTON, NJ 07885 973-

366-2320



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2  
CONTENTS: LITERS

DANGER: REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free from grease and oil. In case of fire, stop leak if safe to do so. Avoid Spills. Do not walk on or roll equipment over spills. Store and use in a well ventilated place. Use only with equipment for compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient

temperature exceeds 52°C/125°F. Container temperature should not exceed 52°C/125°F. Close valve after each use and when empty. Use a back flow preventive device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement. FIRST AID: IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction. CAS:7782-44-7

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

COUNTY WELDING SUPPLY COMPANY 69 E. DEWEY AVE. . WHARTON, NJ 07885 P: 973-366-2320

**OXYGEN,  
REFRIGERATED  
LIQUID USP  
UN 1073**

**CONTENTS: \_\_\_\_\_ LITERS**

CAS NO: 7782-44-7



**DANGER:**

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS  
KEEP CONTAINER IN UPRIGHT POSITION. DO NOT  
CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY  
FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE  
CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH  
LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free  
from grease and oil. In case of fire, stop leak if safe to do so. Avoid  
spills. Do not walk or roll equipment over spills. Store and use in a well



ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52 °C/125 °F. Container temperature should not exceed 52 °C/125 °F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

## **FIRST AID:**

**IN CASE OF FROSTBITE:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**DO NOT REMOVE THIS PRODUCT LABEL.**

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑**

**County Welding Supply**

69 East Dewey Ave.

Wharton, NJ 07885

P: 973-366-2320

**OXYGEN**

oxygen gas

Product Information				
Product Type		HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:60367-002
Route of Administration		RESPIRATORY (INHALATION)		
Active Ingredient/Active Moiety				
Ingredient Name			Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)			OXYGEN	998 mL in 1 L
Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:60367-002-02	37 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1975	
2	NDC:60367-002-03	103 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1975	
Marketing Information				
Marketing Category	Application Number or Monograph Citation		Marketing Start Date	Marketing End Date
NDA	NDA205767		01/01/1975	

**Labeler** - County Welding Supply Co. (042905166)

## Establishment

Name	Address	ID/FEI	Business Operations
County Welding Supply Co.		042905166	manufacture(60367-002)

Revised: 10/2023

County Welding Supply Co.