OXYGEN- oxygen gas Young Welding Supply, Inc

OXYGEN - 2222

OXYGEN COMPRESSED USP LABEL
OXYGEN COMPRESSED USP
UN 1072
PRODUCED BY AIR LIQUEFACTION
OXYGEN-2
18033 (12/14)

WARNING:For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacture in accordance with the Federal Food, Drug, and Cosmetic Act. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. open valve slowly. Close valve after each use and when empty. protect from sunlight when ambient temperature exceeds 52°C (125°F), read and follow the Safety Data Sheet (SDS) before use

CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

YOUNG WELDING SUPPLY, INC

101 E. 1ST STREET • SHEFFIELD, AL 35660

256-383-52429





OXYGEN, REFRIGERATED LIQUID USP LABEL REFRIGERATED LIQUID OXYGEN REFRIGERATED LIQUID, USP

OXYGEN 2

UN 1073

WARNING:For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacture in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction

DANGER

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or forcr fit connections. Avoid spills. Do not walk or roll equipment over spills. Close valve after each use and when empty. Always kep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

YOUNG WELDING SUPPLY, INC

101 E. 1ST STREET • SHEFFIELD, AL 35660

256-383-52429

41533

(01/15)

REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP UN1073



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Ronly.

> Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children

> Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN

CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected

area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL



YOUNG WELDING SUPPLY, INC.

101 E. 1ST STREET • SHEFFIELD, AL 35660 256-383-5429 41533

(01/15)

OXYGEN

Product Information

oxygen gas

| 11 out 1 mornation | | | |
|--------------------|-------------------------|--------------------|----------------|
| Product Type | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:58311-2222 |

Route of Administration RESPIRATORY (INHALATION)

| Active Ingredient/Active Moiety | | |
|---|-------------------|---------------|
| Ingredient Name | Basis of Strength | Strength |
| OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | OXYGEN | 99 L in 100 L |

Packaging

| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
|---|------------------|---|-----------------------------|---------------------------|
| 1 | NDC:58311-2222-1 | 170 L in 1 CYLINDER; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |
| 2 | NDC:58311-2222-2 | 426 L in 1 CYLINDER; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |
| 3 | NDC:58311-2222-3 | 671 L in 1 CYLINDER; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |
| 4 | NDC:58311-2222-4 | 3462 L in 1 CYLINDER; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |
| 5 | NDC:58311-2222-5 | 9300 L in 1 CYLINDER; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |
| 6 | NDC:58311-2222-6 | 169 L in 1 DEWAR; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |
| 7 | NDC:58311-2222-7 | 180 L in 1 DEWAR; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |
| 8 | NDC:58311-2222-8 | 200 L in 1 DEWAR; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |
| 9 | NDC:58311-2222-9 | 7981L in 1 CYLINDER; Type 0: Not a Combination Product | 0 1/0 1/19 6 5 | |

| Marketing Information | | | |
|-----------------------|--|----------------------|--------------------|
| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
| NDA | NDA205767 | 0 1/0 1/19 6 5 | |
| | | | |

Labeler - Young Welding Supply, Inc (034109918)

Registrant - Young Welding Supply, Inc (034109918)

| Establishment | | | | |
|---------------------------|---------|-----------|-------------------------|--|
| Name | Address | ID/FEI | Business Operations | |
| Young Welding Supply, Inc | | 034109918 | manufacture(58311-2222) | |

Revised: 10/2019 Young Welding Supply, Inc