

**OXYGEN - oxygen gas**  
**M & A Welding Supply Co., Inc**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.*

-----

**oxygen**

OXYGEN, COMPRESSED USP UN1072

OXYGEN 2 18033LC (R 03/06)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation.

For all other medical applications, Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration,

without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing

equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in

conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY

ACCELERATES COMBUSTION. Keep oil, grease away. Open valve slowly. Store and use with adequate ventilation. Use only with


equipment cleaned for oxygen service and rated for cylinder pressure. Use back flow preventive device in the piping. Close

valve after each use and when empty. Cylinder temperature should not exceed 52C (125F). Use in accordance with the

Material Safety Data Sheets (MSDS). CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

M and A WELDING SUPPLY CO. 6 WEST AVE. Cartersville, GA 30120 770-386-3207

OXYGEN,  
COMPRESSED  
USP  
UN1072



**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. **Produced by Air**

**Liquefaction. WARNING:** HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

**M & A WELDING SUPPLY CO.**  
6 West Ave. • Cartersville, GA 30120  
770-386-3207

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:53550-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:53550-001-01	7108 L in 1 CYLINDER		
2	NDC:53550-001-02	3540 L in 1 CYLINDER		
3	NDC:53550-001-03	9543 L in 1 CYLINDER		
4	NDC:53550-001-04	2265 L in 1 CYLINDER		

### Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		01/01/1979	

**Labeler** - M & A Welding Supply Co., Inc (033541442)

### Establishment

Name	Address	ID/FEI	Business Operations
------	---------	--------	---------------------

M & A Welding Supply Co., Inc.

033541442

manufacture

Revised: 5/2010

M & A Welding Supply Co., Inc