


**OXYGEN- oxygen gas**  
**Ann Arbor Welding Supply Co., Inc. DBA Arbor Specialty Gases**

-----  
**Oxygen Label**

OXYGEN, COMPRESSED USP  
UN 1072

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Close valve after each use and when empty. Cylinder temperature should not exceed 52 C (125 F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7. RETURN WITH 25 PSIG. DO NOT REMOVE THIS PRODUCT LABEL.

ANN ARBOR WELDING SUPPLY  
4811 CARPENTER ROAD. YPSILANIT, MI 48197  
734-572-0444



OXYGEN, COMPRESSED USP  
UN 1072

Contents LTRS CU.FT.

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. **WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.** Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Close valve after each use and when empty. Cylinder temperature should not exceed 52 C (125 F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7. **DO NOT REMOVE THIS PRODUCT LABEL.**

ANN ARBOR WELDING SUPPLY

4811 CARPENTER ROAD. YPSILANIT, MI 48197


734-572-0444



Produced by air liquefaction  
**OXYGEN, COMPRESSED USP**  
**UN 1072**

**WARNING:** For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. **WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.** Use only with pressure reducing equipment and apparatus designed for Oxygen. Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition. Federal law requires that this container be refilled with oxygen USP only be establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. Pursuant to

recommendations by Compressed Gas Association, do not expose pressured cylinders to temperatures in excess of 125 F. **DO NOT REMOVE THIS PRODUCT LABEL.** Use a back flow preventive device in the piping. Use only in accordance with product instructions and Material Safety Data Sheet.



## REFRIGERATED LIQUID

### OXYGEN, REFRIGERATED LIQUID USP UN1073

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.** Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 C (125 F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS). **FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7782-44-7**

**DO NOT REMOVE THIS PRODUCT LABEL.**

Arbor Specialty Gases

4811 CARPENTER ROAD. YPSILANTI, MI 48197  
866-528-9960



**OXYGEN, REFRIGERATED LIQUID USP UN1073 (CRYOGENIC LIQUID) Produced by Air Liquefaction**  
**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION**  
**WARNING: WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only.  
**WARNING!** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).  
**WARNING:** Caution Federal Law Prohibits Dispensing without Prescription.  
**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately. PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.

Company Name:

Lot Number:

Contents:

Expiration Date:

**DO NOT REMOVE THIS PRODUCT LABEL.**

# OXYGEN

REFRIGERATED LIQUID, U.S.P.  
UN 1073  
(CRYOGENIC LIQUID)

Produced by Air Liquefaction



**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

<p><b>WARNING</b></p> <p><b>WARNING!</b> EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.</p> <p>For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.</p> <p><b>WARNING:</b> Caution Federal Law Prohibits Dispensing without Prescription.</p>	<p><b>WARNING!</b> Uninterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep all greases and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment near spills. Close valve after each use and when empty. Use in accordance with Material Safety Data Sheet.</p>	<p><b>FIRST AID</b></p> <p><b>IN CASE OF FROSTBITE, obtain medical treatment immediately.</b></p> <p><b>PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.</b></p> <p>Company Name: Lot Number: Contents: Expiration Date:</p>
---	---	--

**DO NOT REMOVE THIS PRODUCT LABEL**

OXYGEN, COMPRESSED USP

UN 1072

CONTENTS: LTRS: CU. FT.

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. **DO NOT REMOVE THIS PRODUCT LABEL.**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. C.A.S. NO. 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

Arbor Specialty Gases

A Division of: Ann Arbor Welding Supply

4811 Carpenter Rd. Ypsilanti, MI 48197

734-572-0444

**OXYGEN,  
COMPRESSED  
USP  
UN 1072**



CONTENTS:

LTR: 0  
GAL: 0

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire, stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. DO NOT REMOVE THIS PRODUCT LABEL.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction, C.A.S. NO. 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

**Arbor Specialty Gases**

A Division of  Welding Supply  
4811 Carpenter Rd., Ypsilanti, MI 48197  
734-572-0444



## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:59713-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:59713-001-01	255 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
2	NDC:59713-001-02	142 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
3	NDC:59713-001-03	368 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
4	NDC:59713-001-04	651 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
5	NDC:59713-001-05	680 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
6	NDC:59713-001-06	7108 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	

<b>7</b>	NDC:59713-001-07	9543 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
<b>8</b>	NDC:59713-001-08	10959 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
<b>9</b>	NDC:59713-001-09	623 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
<b>10</b>	NDC:59713-001-10	3539 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
<b>11</b>	NDC:59713-001-11	170 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
<b>12</b>	NDC:59713-001-12	1699 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	
<b>13</b>	NDC:59713-001-13	11659 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/1992	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205827	07/01/1992	

**Labeler** - Ann Arbor Welding Supply Co., Inc. DBA Arbor Specialty Gases (016708778)

## Establishment

Name	Address	ID/FEI	Business Operations
Ann Arbor Welding Supply Co., Inc. DBA Arbor Specialty Gases		016708778	manufacture(59713-001)

Revised: 10/2021

Ann Arbor Welding Supply Co., Inc. DBA Arbor Specialty Gases