

OXYGEN - oxygen gas

Allen's Cylinder Testing & Inspection Company

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, [click here](#).

**OXYGEN,
COMPRESSED
USP**

UN1072



18933 (P. 04/05)

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, **Caution:** Unlimited use of high concentrations of Oxygen over a long duration, without monitoring its effect on apparatus designed arterial blood, may be harmful. Use only with pressure reducing equipment and breathing, unless used in conjunction with resuscitative equipment. **Produced by Air Liquelation.**

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION! Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the **Material Safety Data Sheet (MSDS)**. **DO NOT REMOVE THIS PRODUCT LABEL.**

MANUFACTURED BY:
ALLENS CTI
5206 INDUSTRIAL WAY SUITE B • ANDERSON, CA 95907
CAS: 7782-44-7 (530) 378-5196

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high-concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction.**

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the **Material Safety Data Sheet (MSDS).**

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

Manufactured By:

Allens CTI

5206 Industrial Way Suite B, Anderson, CA 96007

(530) 378-5196

OXYGEN				
oxygen gas				
Product Information				
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:49790-001	
Route of Administration	RESPIRATORY (INHALATION)			
Active Ingredient/Active Moiety				
	Ingredient Name	Basis of Strength	Strength	
	Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	992 mL in 1 L	
Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:49790-001-01	42 L in 1 CYLINDER		
2	NDC:49790-001-02	113 L in 1 CYLINDER		
3	NDC:49790-001-03	170 L in 1 CYLINDER		
4	NDC:49790-001-04	198 L in 1 CYLINDER		
5	NDC:49790-001-05	255 L in 1 CYLINDER		
6	NDC:49790-001-06	425 L in 1 CYLINDER		
7	NDC:49790-001-07	623 L in 1 CYLINDER		
8	NDC:49790-001-08	680 L in 1 CYLINDER		
9	NDC:49790-001-09	1699 L in 1 CYLINDER		
10	NDC:49790-001-10	2549 L in 1 CYLINDER		
11	NDC:49790-001-11	3455 L in 1 CYLINDER		
12	NDC:49790-001-12	4248 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		11/04/2009	

Labeler - Allen's Cylinder Testing & Inspection Company (005292460)

Establishment

Name	Address	ID/FEI	Business Operations
Allen's Cylinder Testing & Inspection Company		005292460	manufacture

Revised: 11/2009

Allen's Cylinder Testing & Inspection Company