

OXYGEN- oxygen gas
EWS Welding Supply, Inc.

oxygen

OXYGEN, COMPRESSED U.S.P UN1072 Rx ONLY

PRODUCED BY AIR LIQUIFACTION

Container Filled By Medical Produce Division

OXYGEN 2

DANGER: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Close valve after each use and when empty. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use and store cylinder in use and storage and use in accordance with MSDS. Use protective valve cap when not in use, if provided. Uninterrupted use of high concentrations of oxygen over five hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS, RX ONLY.

DO NOT REMOVE THIS LABEL

NET STATEMENT OF QUANTITY PRESSURE PSIG@70 degrees F Size Contents Liters

EWSWELDING.COM

EWS Welding Supply, Inc.

1161 McCabe,

Elk Grove, IL 60007

Ph: 847-290-1070

Fx: 847-290-1692

OXYGEN
COMPRESSED
U.S.P.
UN 1072
RX ONLY

DANGER: HIGH PRESSURE OXIDIZING GAS.
VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Close valve after each use and when empty. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. User shall secure cylinder in use and storage and use in accordance with MSDS. Use protective valve cap when not in use, if provided.

Uninterrupted use of high concentrations of oxygen over five hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

OXYGEN
2

FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS, RX ONLY.

PRODUCED BY AIR LIQUIFACTION

Container Filled By
 Medical Product Division

DO NOT REMOVE THIS LABEL

NET STATEMENT OF QUANTITY

Pressure

PSIG
 @ 70°F

Size

Contents

Liters

EWS WELDING.COM EWS Welding Supply, Inc.
 1161 McCabe, Elk Grove, IL 60007
 Ph: 847-290-1070 Fx: 847-290-1692

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

OXYGEN, REFRIGERATED LIQUID USP UN1073

PRODUCED BY AIR LIQUIFACTION

Rx ONLY

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Container Filled by Medical Product Division.

DANGER: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. MAY CAUSE SEVERE FROSTBITE. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Keep away from heat, flame and sparks. Keep oil and combustibles away. Open valve slowly. Close valve after each use and when empty. Use only with equipment cleaned for oxygen service and in accord with manufacturer's operating instruction for this container and Material Safety Data Sheet (MSDS).

Do not drop. Use hand truck or specially designed undercarriage for cylinder movement. Avoid spills. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield or goggles and gloves. Do not walk on or roll equipment over spills. Store and use with adequate ventilation to prevent oxygen accumulation.

Uninterrupted use of high concentrations of oxygen over five hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

DO NOT REMOVE THIS PRODUCT LABEL

WARNING: Secure all cylinders while in storage and use.

NET STATEMENT OF QUANTITY Size Contents Liters

EWSWELDING.COM
 EWS Welding Supply, Inc.
 1161 McCabe,
 Elk Grove, IL 60007
 Ph: 847-290-1070
 Fx: 847-290-1692

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

OXYGEN
 REFRIGERATED
 LIQUID U.S.P.
 UN 1073

PRODUCED BY
 AIR LIQUIFACTION
 RX ONLY

WARNING
 FOR EMERGENCY USE
 ONLY WHEN
 ADMINISTERED BY
 PROPERLY TRAINED
 PERSONNEL FOR
 OXYGEN DEFICIENCY
 AND RESUSCITATION.
 FOR ALL OTHER
 MEDICAL APPLICATIONS, RX ONLY.

Container Filled By
 Medical Product Division




DANGER: EXTREMELY COLD OXIDIZING LIQUID AND GAS
 VIGOROUSLY ACCELERATES COMBUSTION. MAY CAUSE SEVERE
 FROSTBITE. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY
 EXPLODE ON IGNITION OR IMPACT.

Keep away from heat, flame and sparks. Keep oil and combustibles away.
 Open valve slowly. Close valve after each use and when empty. Use only with
 equipment cleaned for oxygen service and in accord with manufacturer's
 operating instructions for this container and Material Safety Data Sheet.
 (MSDS)

Do not drop. Use hand truck or specially de-
 signed undercarriage for cylinder movement.
 Avoid spills. Do not get liquid in eyes, on skin or
 clothing. For liquid withdrawal, wear face shield or
 goggles and gloves Do not walk on or roll equipment
 over spills. Store and use with adequate ventilation to
 prevent oxygen accumulation.

Uninterrupted use of high concentrations of oxygen over
 five hours may be harmful. Do not attempt to use on patients
 who have stopped breathing, unless used in conjunction with
 resuscitative equipment.

**FIRST AID: IN CASE OF FROSTBITE, obtain
 medical treatment immediately.**

DO NOT REMOVE THIS LABEL

WARNING: Secure all cylinders while in storage and use.

NET STATEMENT OF QUANTITY

Size

Contents

Liters

EWSWELDING.COM EWS Welding Supply, Inc.
 1161 McCabe, Elk Grove, IL 60007
 Ph: 847-290-1070 Fx: 847-290-1692

OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:62377-0 11
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:62377-011-01	45 L in 1 CYLINDER		
2	NDC:62377-011-02	113 L in 1 CYLINDER		
3	NDC:62377-011-03	165 L in 1 CYLINDER		
4	NDC:62377-011-04	210 L in 1 CYLINDER		
5	NDC:62377-011-05	416 L in 1 CYLINDER		
6	NDC:62377-011-06	685 L in 1 CYLINDER		
7	NDC:62377-011-07	1732 L in 1 CYLINDER		
8	NDC:62377-011-08	3541 L in 1 CYLINDER		
9	NDC:62377-011-09	7111 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141396	01/01/1995	

Labeler - EWS Welding Supply, Inc. (051075653)**Establishment**

Name	Address	ID/FEI	Business Operations
EWS Welding Supply, Inc.		051075653	manufacture

Revised: 11/2015

EWS Welding Supply, Inc.