

**OXYGEN- oxygen gas**  
**Seaboard Welding Supply, Inc.**

-----  
**Oxygen**

**OXYGEN COMPRESSED USP label**

OXYGEN COMPRESSED USP

UN 1072

PRODUCED BY AIR LIQUEFACTION

OXYGEN-2 PRODUCED BY AIR LIQUEFACTION

18033 (12/14)

WARNING:For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacture in accordance with the Federal Food, Drug, and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. open valve slowly. Close valve after each use and when empty. protect from sunlight when ambient temperature exceeds 52°C (125°F). read and follow the Safety Data Sheet (SDS) before use

CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

SEABOARD WELDING SUPPLY, INC.

2112 KINGS HWY • OAKHURST, NJ 07755

732-493-8100



## **OXYGEN REFRIGERATED LIQUID, USP label**

OXYGEN REFRIGERATED LIQUID, USP

UN 1073

**OXYGEN 2**

**(R-K14)**

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

### **WARNING**

#### **USP**

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

#### **Produced by Air Liquefaction**

Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacture in accordance with the Federal Food, Drug, and Cosmetic Act.

### **DANGER**

**MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.**

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid

spills. Do not walk or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.

**READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.**

**CAS 7782-44-7**

**FIRST AID**

**IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.**

Lot Number:

Contents:

Expiration Date:

**SEABOARD WELDING SUPPLY, INC.**

**2112 KINGS HWY • OAKHURST, NJ 07755**

**732-493-8100**



**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

<p><b>WARNING</b></p> <p><b>USP</b></p> <p>For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.</p> <p>Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.</p> <p><b>Produced by Air Liquefaction.</b></p> <p>Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.</p> <p><b>READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.</b></p> <p>CAS: 7782-44-7</p>	<p><b>DANGER</b></p> <p><b>MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.</b></p> <p>Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. <b>DO NOT</b> change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.</p>	<p><b>FIRST AID</b></p> <p><b>IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.</b></p> <p>Lot Number:</p> <p>Contents:</p> <p>Expiration Date:</p>
---	---	---

**Seaboard Welding Supply Inc.**  
2112 Kings Hwy  
Oakhurst NJ 07755  
732 - 493 - 8100

## OXYGEN

oxygen gas

### Product Information

**Product Type**

HUMAN PRESCRIPTION DRUG

**Item Code (Source)**

NDC:42139-001

**Route of Administration** RESPIRATORY (INHALATION)

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42139-001-01	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
2	NDC:42139-001-02	139 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
3	NDC:42139-001-03	248 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
4	NDC:42139-001-04	426 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
5	NDC:42139-001-05	671 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
6	NDC:42139-001-06	647 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
7	NDC:42139-001-07	1724 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
8	NDC:42139-001-08	3462 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
9	NDC:42139-001-09	6896 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
10	NDC:42139-001-10	8496 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1988	
11	NDC:42139-001-11	196 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1988	
12	NDC:42139-001-12	300 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1988	

### Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1988	

**Labeler** - Seaboard Welding Supply, Inc. (001913912)

**Registrant** - Seaboard Welding Supply, Inc. (001913912)

### Establishment

Name	Address	ID/FEI	Business Operations
Seaboard Welding Supply, Inc.		001913912	manufacture(42139-001)

