MEDICAL AIR- oxygen gas Norco, Inc.

-----

#### MEDICAL AIR USP LABEL AIR COMPRESSED

#### **MEDICAL AIR USP**

AIR, COMPRESSED NON-FLAMMABLE GAS 2 41002 (R 08/09) (19.5%-23% Oxygen, 77%-80.5% Nitrogen)

#### **UN1002**

**WARNING:** For breathing support when used by properly trained personnel. For medical applications, Rx only.

Administration of Medical Air may be hazardous or contraindicated. For use only by or under the supervision

of a licensed practitioner who is experienced in the use and administration of Medical Air and is familiar with

the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards,

contraindications, and side effects and the precautions to be taken.

Lot No. Cyl. Size Contents CF

T 310 ft3 K 230 ft3 E 23 ft3

**WARNING:** HIGH PRESSURE GAS. MAY ACCELERATE COMBUSTION.

Keep oil and grease away. Use equipment rated for cylinder pressure. Cylinder temperature should not exceed

52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in

the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: OXYGEN 7782-44-7 NITROGEN: 7727-37-9

#### DO NOT REMOVE THIS PRODUCT LABEL

NORCO, INC. 898 W. Gowen Rd Boise, ID 83705 208-336-1643

USPUN1002

# MEDICAL AIR USP

# AIR, COMPRESSED

(19.5%-23% Oxygen, 77% - 80.5% Nitrogen)



UN1002

WARNING: For breathing support when used by properly trained personnel. For medical applications, Rx only.

Administration of Medical Air may be hazardous or contraindicated. For use only by or under the supervision of a licensed practioner who is experienced in the use and administration of Medical Air and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken.

Lot No.	Cyl. Size	Contents CF
	T	310 ft <sup>3</sup>
	K	230 ft <sup>3</sup>
	E	23 ft³

WARNING: HIGH PRESSURE GAS. MAY ACCELERATE COMBUSTION.

Keep oil and grease away. Use equipment rated for cylinder pressure. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: OXYGEN 7782-44-7 NITROGEN: 7727-37-9 DO NOT REMOVE THIS PRODUCT LABEL



NORCO, INC. 898 W. Gowen Rd. • Boise, ID 83705 208-336-1643

USPUN1002

# **MEDICAL AIR**

oxygen gas

#### **Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:42602-004
---------------------	-------------------------	--------------------	---------------

**Route of Administration** RESPIRATORY (INHALATION)

8779.2 L in 1 CYLINDER; Type 0: Not a

**Combination Product** 

# **Active Ingredient/Active Moiety**

Ingredient Name		Basis of Strength	Strength
	OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	23 L in 100 L

### **Inactive Ingredients**

Ingredient Name	Strength

09/01/2008

NITROGEN (UNII: N762921K75)

3 NDC:42602-

004-03

#### **Packaging Marketing Start Marketing End** # Item Code **Package Description Date** Date 1 NDC:42602-651.36 L in 1 CYLINDER; Type 0: Not a 09/01/2008 004-01 **Combination Product** 2 NDC:42602-004-02 6513.6 L in 1 CYLINDER; Type 0: Not a 09/01/2008 **Combination Product**

Marketing Information			
Marketing Category			Marketing End Date
NDA	NDA205820	09/01/2008	

### **Labeler -** Norco, Inc. (043694645)

# **Registrant - Norco**, Inc. (043694645)

Establishment			
Name	Address	ID/FEI	Business Operations
Norco, Inc.		962460528	manufacture(42602-004)

Revised: 11/2023 Norco, Inc.