

OXYGEN- oxygen gas
Super Gas, Inc.

Oxygen

OXYGEN, COMPRESSED USP

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheet (SDS) before use.

CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WAGNER WELDING SUPPLY 10 GAY STREET LONGMONT, CO 80501 303-776-1491

CONTENTS: LTRS CU. FT.


UN1072

PRODUCED BY AIR LIQUEFACTION

OXYGEN 2

17033 (12/14)

PICTOGRAM GHS04 GAS CYLINDER



OXYGEN, REFRIGERATED LIQUID USP UN1073

OXYGEN 2

Rx only

WARNING: For emergency use only when administered by properly administered personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold-insulating gloves, face shield and eye protection. In case of fire: Stop leak if safe to do so. Use a back-flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF ON SKIN:** thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.


WAGNER WELDING SUPPLY 10 GAY STREET LONGMONT, CO 80501

303-776-1491

41550 (12/14)

PICTOGRAM GHS04 GAS CYLINDER

**OXYGEN,
REFRIGERATED
LIQUID
USP
UN1073**



R_x only

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R_x only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.
Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF ON SKIN:** thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7



DO NOT REMOVE THIS PRODUCT LABEL.

WAGNER WELDING SUPPLY
10 GAY STREET • LONGMONT, CO 80501
303-776-1491

41550 (12/14)

OXYGEN, COMPRESSED USP

UN1072

OXYGEN 2

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R_x only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors


or in well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheets (0) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

WAGNER WELDING SUPPLY 10 GAY STREET LONGMONT, CO 80501 303-776-1491

**OXYGEN,
COMPRESSED
USP**

UN1072

Produced by Air Liquefaction




WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal *Food, Drug, and Cosmetic Act*.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (0) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



WAGNER WELDING SUPPLY
10 GAY STREET • LONGMONT, CO 80501
303-776-1491

40035
(01/15)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:61128-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	992 L in 1000 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:61128-001-01	8080 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
2	NDC:61128-001-02	4040 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
3	NDC:61128-001-03	2380 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
4	NDC:61128-001-04	705 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
5	NDC:61128-001-05	425 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
6	NDC:61128-001-06	212 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
7	NDC:61128-001-07	129280 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	
8	NDC:61128-001-08	120327 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	
9	NDC:61128-001-09	30935 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205712	12/01/2007	

Labeler - Super Gas, Inc. (832100437)

Establishment

Name	Address	ID/FEI	Business Operations
Super Gas, Inc.		832100437	manufacture(61128-001)