OXYGEN- oxygen gas Acute Care Gases II, LLC

Oxygen

Oxygen - Albany

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2



DANGER: COMPRESSED, OXIDING GAS. MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications. **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure. Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects free of oil and grease to avoid ignition Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 52^OC/125^OF. Use a back-flow preventative device in the piping. Federal law requires that the container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Use only in accordance with product instructions and material safety data sheet. Keep and store away from heat/sparks/open flame/combustible materials. No smoking. Store and use in a cool, well ventilated place.

DO NOT REMOVE THIS LABEL CAS 7782-44-7 Size & Contents M6 C / M9 D Ε Н Other 170 Liters 248 Liters 415 Liters 682 Liters 6910 Liters Liters П П

Acute Care Gases II, LLC

25 Walker Way 2c Albany, NY 12205 855-399-1224

OXYGEN, COMPRESSED USP **UN 1072** OXYGEN

DANGER:

COMPRESSED, OXIDIZING GAS. MAY CAUSE OR INTENSIFY FIRE: OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: Rx ONLY.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure. Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects free of oil and grease to avoid ignition. Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 52 °C/125°F. Use a back flow preventative device in the piping. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Use only in accordance with product instructions and material safety data sheet. Keep and store away from heat/sparks/open flame/combustible materials. No Smoking. Store and use in a cool, well ventilated place.

DO NOT REMOVE THIS LABEL

CAS NO: 7782-44-7 Other H C/M9 D E M6 170 Liters 248 Liters 415 Liters 682 Liters 6910 Liters ___

Acute Care Gases II, LLC

25 Walker Way 2c Albany, NY 12205 855-399-1224

Oxygen Refrigerated **OXYGEN, REFRIGERATED LIQUID USP UN1073**

OXYGEN, U.S.P. OXYGEN 2



Contents Liters

CAS NO: 7782-44-7

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBELS IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment. Produced by Air Liquefaction

© Applied Home Healthcare Equipment 2014

Acute Care Gases of CT LLC

23 Nutmeg Valley Road Wolcott, CT 06716 855-399-1224

OXYGEN, REFRIGERATED LIQUID USP

UN 1073

CONTENTS: _____LITERS

CAS NO: 7782-44-7



MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS
REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR
INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY
EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub.

affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Px only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Acute Care Gases of CT LLC 23 Nutmeg Valley Road Wolcott, CT 06716 855-399-1224

Oxygen 15 Cubic Feet
OXYGEN, COMPRESSED USP UN 1072 Produced by Air Liquefaction
OXYGEN 2 133445 (06/19)



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.



CONTENTS: 15 CUBIC FEET

ACG ACUTE CARE GASES OF CT, LLC

ACUTE CARE 23 NUTMEG VALLEY RD • WOLCOTT, CT 06716

GASES 855-399-1224



Oxygen 24 cubic feet OXYGEN, COMPRESSED USP UN 1072 Produced by Air Liquefaction OXYGEN 2 133445 (06/19)



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not

attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.



CONTENTS: 24 CUBIC FEET

ACG ACUTE CARE GASES OF CT, LLC

ACUTE CARE 23 NUTMEG VALLEY RD • WOLCOTT, CT 06716

GASES 855-399-1224



Oxygen Compressed - Wolcott
OXYGEN, COMPRESSED USP UN1072
OXYGEN 2



DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS LABEL

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications. **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

© Applied Home Healthcare Equipment 2014

CAS 7782-44-7

Contents	Size
113 Liters	□ M4
165 Liters	□ M6
255 Liters	□ C
425 Liters	□ D
680 Liters	□ E
7080 Liters	H
Liters	☐ Other

Acute Care Gases of CT, LLC

23 Nutmeg Valley Road Wolcott, CT 06716 855-399-1224

OXYGEN, COMPRESSED USP **UN 1072**

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE: MAY EXPLODE IF HEATED.



Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use,

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction, GApplied Home Healthcare Equipment 2014

Contents	Size
113 Liters	□ M4
165 Liters	□ M6
255 Liters	ОС
425 Liters	□ D
680 Liters	DE
7080 Liters	□н
Liters	□ Other

CAS NO: 7782-44-7

Acute Care Gases of CT, LLC

23 Nutmeg Valley Road Wolcott, CT 06716 855-399-1224

Oxygen - Lakeland 15 cubic

OXYGEN, COMPRESSED USP UN 1072 Produced by Air Liquefaction

OXYGEN 2 143654 (04/21)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

ACG ACUTE CARE GASES OF FL, LLC

ACUTE CARE 4040 Kidron Road Unit 7

GASES Lakeland, FL 33811 • 855-399-1224

CONTENTS: 15 CUBIC FEET



Oxygen - Lakeland 24 cubic

OXYGEN, COMPRESSED USP UN 1072 Produced by Air Liquefaction

OXYGEN 2 143655 (04/21)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not

attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

ACG ACUTE CARE GASES OF FL, LLC

ACUTE CARE 4040 Kidron Road Unit 7

GASES Lakeland, FL 33811 • 855-399-1224

CONTENTS: 24 CUBIC FEET



OXYGEN

oxygen gas

Product Information			
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:69240-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety		
Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

P	Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date	
1	NDC:69240- 001-01	170 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014		
,	NDC:69240-	248 L in 1 CYLINDER; Type 0: Not a Combination	00/01/2014		

	001-02	Product	U9/U1/2U14	
3	NDC:69240- 001-03	415 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	
4	NDC:69240- 001-04	682 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	
5	NDC:69240- 001-05	6910 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	
6	NDC:69240- 001-06	425 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	

Marketing Information				
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date	
NDA	NDA205767	09/01/2014		

Labeler - Acute Care Gases II, LLC (080309021)

Establishment			
Name	Address	ID/FEI	Business Operations
Acute Care Gases II, LLC		080309021	manufacture(69240-001)

Establishment			
Name	Address	ID/FEI	Business Operations
Acute Care Gases of CT LLC		011527667	manufacture(69240-001)

Establishment			
Name	Address	ID/FEI	Business Operations
Acute Care Gases of MA LLC		117135641	manufacture(69240-001)

Establishment					
Name	Address	ID/FEI	Business Operations		
Acute Care Gases of FI LLC		118012268	manufacture(69240-001)		

Revised: 10/2023 Acute Care Gases II, LLC