# NITROGEN - nitrogen gas American Welding & Gas

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

-----

## Nitrogen

NITROGEN, COMPRESSED

UN1066

7727-37-9

NITROGEN, NF

Pressure: \_\_\_\_\_ PSIG at 70°F

Size: \_\_\_\_\_

Contents: Liters

DO NOT REMOVE THIS PRODUCT LABEL.

Rx Only. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced the use and frequency and duration of administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken.

CAUTION: HIGH PRESSURE GAS. CAN CAUSE RAPID SUFFOCATION. Store and use with adequate ventilation. Use equipment rated for cylinder pressure. Use a back flow preventive device in the piping. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS).

### FIRST AID:

IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

TO BE REFILLED BY AN INWELD AUTHORIZED FACILITY ONLY. RETURN WITH 25 PSIG



REFRIGERATED LIQUID NITROGEN, REFRIGERATED LIQUID NF UN1977

### ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

Rx only

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE.

CAN CAUSE RAPID SUFFOCATION. CAN CAUSE SEVER FROSTBITE.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Cylinder temperature should not exceed 52C (125F).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.

AMERICAN WELDING and GAS WILLMAR, MN 56201 320-235-4774



# NITROGEN. REFRIGERATED LIQUID NF



UN1977

### 1 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. 1

### R only

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of littingen and is familiar with the indications, effects, desages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE.

CAN CAUSE RAPID SUFFOCATION. CAN CAUSE SEVERE PROSTBITE.

Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or debthing.
For liquid withdrawal, wear face shield and gloves.
De not drop, Use suitable hand truck for container movement.

De recturge, use anabore man ruce not consider movemen. Dylinder temperature should not exceed \$2.0 (125.F). Close valve after each use and when smpty. Use a back flow preventive device in the ptyring. Use in accordance with the Material Safety Data Sheet. (MSDS).

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IN CASE OF PROSTBITE, obtain medical treatment immediately.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.

### **AMERICAN WELDING & GAS**

WILLMAR, MN 56201 320-235-4774

435-49 (06/06)

Product Information

Product Type HUMAN PRESCRIPTION DRUG LABEL Item Code (Source) NDC:44076-006

Route of Administration RESPIRATORY (INHALATION) DEA Schedule

Basis of Strength	Strength
n	990 mL in 1 L
]	<b>Basis of Strength</b>

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:44076-006-15	255 L in 1 CYLINDER		
2	NDC:44076-006-16	3640 L in 1 DEWAR		
3	NDC:44076-006-17	4551 L in 1 DEWAR		
4	NDC:44076-006-18	3588 L in 1 DEWAR		
5	NDC:44076-006-19	5658 L in 1 DEWAR		
6	NDC:44076-006-20	3685 L in 1 DEWAR		
7	NDC:44076-006-21	4099 L in 1 DEWAR		

Marketing Information				
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date	
unapproved medical gas		04/01/2007		

# Labeler - American Welding & Gas (068181965)

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		832328061	manufacture(44076-006)

Establishment				
Name	Address	ID/FEI	<b>Business Operations</b>	
American Welding & Gas		068181965	manufacture(44076-006)	

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		806534954	manufacture(44076-006)

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		151002222	manufacture(44076-006)

Revised: 2/2014 American Welding & Gas