

**OXYGEN - oxygen gas**  
**Vagabond Welding Supply**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.*

-----  
**OXYGEN COMPRESSED USP SL**

OXYGEN COMPRESSED USP UN1072 OXYGEN 2 18033 (R 04/05)

**WARNING:** For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.


**WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.** Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 ° C (125 ° F).

Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: 7782-44-7  
DO NOT REMOVE THIS PRODUCT LABEL

Vagabond Welding Supply

55870 Yucca Trail Yucca Valley, CA 92284 (760) 365-3070



## **OXYGEN COMPRESSED USP**

OXYGEN COMPRESSED USP UN1072 OXYGEN 2

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

**Caution:** Federal law prohibits dispensing without prescription.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING:**HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 ° C (125 ° F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL**

Vagabond Welding Supply

55870 Yucca Trail Yucca Valley, CA 92284 (760) 365-3070

40035 (R 01/05)

# OXYGEN, COMPRESSED USP

**UN1072**



**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **O<sub>2</sub>** only. **Caution:** Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**WARNING:** HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

## Vagabond Welding Supply

55870 Yucca Trail • Yucca Valley, CA 92284  
(760)365-3070

40035  
(R 01/05)

## **REFRIGERATED OXYGEN USP**

### **REFRIGERATED LIQUID**

**OXYGEN REFRIGERATE LIQUID USP UN1073 OXYGEN 2**

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.  
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.  
VIGOROUSLY ACCELERATES COMBUSTION.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE OR IGNITION OR IMPACT  
CAN CAUSE SEVERE FROSTBITE.**

Keep oil, grease, and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin, or clothing.  
For liquid withdraw, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Cylinder temperature should not exceed 52° C (125° F).  
Close valve after each use and when empty.  
Use a back flow preventive device in the piping.  
Use in accordance with the Material Safety Data Sheet (MSDS).

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

**DO NOT REMOVE THIS LABEL**

Vagabond Welding Supply

55870 Yucca Valley, CA 92284 (760) 365-3070

41533 (R 10/04)

**REFRIGERATED LIQUID**

**OXYGEN**



# OXYGEN, REFRIGERATED LIQUID USP

UN1073



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑**  
**DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

### **Produced by Air Liquefaction.**

**WARNING:** EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.  
VIGOROUSLY ACCELERATES COMBUSTION.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.  
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin, or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Cylinder temperature should not exceed 52°C (125°F).

Cylinder temperature exceeds the intended use.  
Close valve after each use and when empty.  
Use a back flow preventive device in the piping.  
Use in accordance with the **Material Safety Data Sheet (MSDS)**.

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

## Vagabond Welding Supply

55870 Yucca Trail • Yucca Valley, CA 92284  
(760)365-3070

41533  
(R 10/04)

### OXYGEN

oxygen gas

#### Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:58 162-100
Route of Administration	RESPIRATORY (INHALATION)		

#### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

#### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:58 162-100-01	420 L in 1 CYLINDER		
2	NDC:58 162-100-02	690 L in 1 CYLINDER		
3	NDC:58 162-100-03	3160 L in 1 CYLINDER		
4	NDC:58 162-100-04	5270 L in 1 CYLINDER		
5	NDC:58 162-100-05	6900 L in 1 CYLINDER		
6	NDC:58 162-100-06	7060 L in 1 CYLINDER		
7	NDC:58 162-100-07	8510 L in 1 CYLINDER		
8	NDC:58 162-100-08	113.3 L in 1 CYLINDER		
9	NDC:58 162-100-09	164.5 L in 1 CYLINDER		

10	NDC:58 162-100-10	139 L in 1 CYLINDER		
11	NDC:58 162-100-11	248.4 L in 1 CYLINDER		
12	NDC:58 162-100-12	647.1 L in 1 CYLINDER		
13	NDC:58 162-100-13	1723.6 L in 1 CYLINDER		
14	NDC:58 162-100-50	17248 L in 1 DEWAR		
15	NDC:58 162-100-51	26650 L in 1 DEWAR		
16	NDC:58 162-100-52	86055 L in 1 DEWAR		
17	NDC:58 162-100-53	137667 L in 1 DEWAR		
18	NDC:58 162-100-54	145340 L in 1 DEWAR		
19	NDC:58 162-100-55	154800 L in 1 DEWAR		
20	NDC:58 162-100-56	172000 L in 1 DEWAR		

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		04/01/2013	

**Labeler** - Vagabond Welding Supply (104055702)

**Registrant** - Vagabond Welding Supply (104055702)

## Establishment

Name	Address	ID/FEI	Business Operations
Vagabond Welding Supply		104055702	manufacture(58 162-100)

## Establishment

Name	Address	ID/FEI	Business Operations
Air Liquide Healthcare America Corporation		067631762	manufacture(58 162-100)

## Establishment

Name	Address	ID/FEI	Business Operations
California Tool and Welding Supply, LLC		070941877	manufacture(58 162-100)

Revised: 5/2013

Vagabond Welding Supply