OXYGEN- oxygen gas Depke Welding Supplies, Inc.

Oxygen

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

CONTENTS: T-323 CF K-238CF E, M-118 CF Q-81 CF M60-57 CF E Pur-23 CF DD-22 CF D Pur-14 CF M9-8.5 CF M6-5.7 CF

Depke GASES AND WELDING SUPPLIES 628 E WILLIAMS ST DANVILLE, IL 61832 1-800-38-DEPKE



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2 CONTENTS: LTRS: CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

Depke GASES AND WELDING SUPPLIES 628 E WILLIAMS ST DANVILLE, IL 61832 1-800-



TIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

> P GASES AND WELDING SUPPLIES 1-800-38-DEPKE

628 E WILLIAMS ST DANVILLE, IL 61832 47136 (01/15)

38-DEPKE

0)	XYGEN						
oxygen gas							
Ρι	Product Information						
Product Type			HUMAN PRESCRIPTION DRUG	tem Code (Source)	NDC:10690-001		
Ro	Route of Administration		RESPIRATORY (INHALATION)				
Ac	tive Ingred		-				
		Ingredie	ent Name	Basis of Strength	Strength		
ОХ	OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)			OXYGEN	995 mL in 1 L		
Pa	ackaging						
#	ltem Code	Pa	ackage Description	Marketing Start Date	Marketing End		
1	NDC:10690-			Date	Date		
	001-01	163 L in 1 CYL Product	NDER; Type 0: Not a Combination	01/01/1978	Date		
2		Product	NDER; Type 0: Not a Combination		Date		
2 3	001-01 NDC:10690-	Product 236 L in 1 CYLI Product		01/01/1978 01/01/1978	Date		
_	001-01 NDC:10690- 001-02 NDC:10690-	Product 236 L in 1 CYLI Product 396.43 L in 1 C Product	NDER; Type 0: Not a Combination	01/01/1978 01/01/1978 01/01/1978	Date		

	Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
Μ	arketing	Information		
16	NDC:10690- 001-16	200 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1978	
15	NDC:10690- 001-15	160 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1978	
14	NDC:10690- 001-14	945188.026 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1978	
13	NDC:10690- 001-13	621413.201 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1978	
12	NDC:10690- 001-12	387855.849 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1978	
11	NDC:10690- 001-11	235926.905 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1978	
10	NDC:10690- 001-10	162963.452 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1978	
9	NDC:10690- 001-09	127425.8 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1978	
8	NDC:10690- 001-08	9344.5 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1978	
7	NDC:10690- 001-07	6739.34 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1978	
6	NDC:10690- 001-06	3341.3 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1978	
Э	001-05	Combination Product	01/01/12/0	

Category	Citation	Date	Date
NDA	NDA205865	01/01/1978	

Labeler - Depke Welding Supplies, Inc. (025382276)

Establishment

Name	Address	ID/FEI	Business Operations
DEPKE WELDING SUPPLIES, INC.		025382276	manufacture(10690-001)

Name	Address	ID/FEI	Business Operations
PRATT SUPPLIES INC. dba Depke Welding Supplies, Inc		025565821	manufacture(10690-001)

Establishment				
Name	Address	ID/FEI	Business Operations	
DEPKE WELDING SUPPLIES INC		041939869	manufacture(10690-001)	

Revised: 10/2023

Depke Welding Supplies, Inc.