OXYGEN - oxygen gas The Service Center LLC

Oxygen

US1072 OXYGEN, COMPRESSED USP Medical Gas DO NOT REMOVE THIS PRODUCT LABEL

OXYGEN 2

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Do not smoke. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only be establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

CAS: 7782-44-7.
PRODUCED BY AIR LIQUEFACTION
THE SERVICE CENTER LLC

BROADVIEW, IL 60155-2817

DANGER! MAY CAUSE OR INTENSIFY FIRE: OXIDIZER, CONTINUES GAS UNDER PRESSURE: MAY CAUSE OR INTENSIFY FIRE: OXIDIZER, CONTINUES GAS UNDER PRESSURE: MAY EXPLODE IF HEATED, Do not handle with an extent pol have been read and understood. Keep and store away from On valves and filtings tree from grease and oil. Do not smoke. well-verificated place. In case of fire stop leak it safe to do so, lise a to piping. Use only with equipment of compatible materials of conessure. Use only with equipment cleaned for coppin serial valve after each use and when empty. Protect from such exceeds 52°C (125°F). Read and follow the Salety Date Sheet (225) told Medical Gas WARNINGS or emergency use only when administered by DO NOT REMOVE THIS LABEL deficiency and respectation. For all other medical applications PRODUCED BY MR LYCKERATION CAS. 7182-44-7 THE SERVICE CENTER LLC. BROATNIEN, L. 60156 concentrations of onyon over a long duration, without conditioning as execu-be formful. Up not afternet to use on patients who have stopped breathing unless us equipment, Federal Law requires that this container be reflied with oxyon USP only by establiate accordance with the Lawrence ance with the Federal Food, Drug, and Cosmetic Act.

OXYGEN, REFRIGERATED LIQUID USP UN1073
MEDICAL GAS
Produced by Air Liquefaction.
OXYGEN 2
CONTENTS: Liquid

Liters When Full

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Do not smoke. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Extremely cold oxidizing liquid may explode on ignition or impact. Can cause severe frostbite. Do not get liquid in eyes, on skin or on clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on, or roll equipment over spills. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

WARNING: USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only be establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

FIRST AID: In case of frostbite, obtain medical attention immediately.

DO NOT REMOVE THIS PRODUCT LABEL.

THE SERVICE CENTER LLC




ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

DANGER! MAY CAUSE OR INTENSIFY FIRE: OXIDIZER, CONTAINS GAS UNDER PRESSURE: MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and filtings free from grease and oil. Do not smoke. Use and store only outdoors or in a well-ventilated place. In case of fire: stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Extremely cold oxidizing liquid and gas under pressure. Vigorously accelerates combustion. Combustibles in contact with liquid may explode on ignition or impact. Can cause severe frostbite. Do not get liquid in eyes, on skin or on clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on, or roll equipment over spills. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effects on oxygen content of arterial blood may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Federal Law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

FIRST AID: In case of frostbite, obtain medical attention immediately.

DO NOT REMOVE This label



CAS. 7782-44-7

BROADVIEW, IL 60155-2817

OXYGEN

oxygen gas

Product TypePRESCRIPTION ANIMAL DRUGItem Code (Source)NDC:67024-011

Route of Administration RESPIRATORY (INHALATION)

Active Ingredient/Active Moiety

ı	Ingredient Name	Dasis of Strength	Strength
I	Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	992 mL in 1 L

-	. 1		•
	20	770	ima
	au	Nas	ing

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
---	-----------	---------------------	----------------------	--------------------

NDC:67024-011-01	680 L in 1 CYLINDER		
NDC:67024-011-02	415 L in 1 CYLINDER		
NDC:67024-011-03	650 L in 1 CYLINDER		
NDC:67024-011-04	248 L in 1 CYLINDER		
NDC:67024-011-05	165 L in 1 CYLINDER		
NDC:67024-011-06	170 L in 1 CYLINDER		
NDC:67024-011-07	198 L in 1 CYLINDER		
NDC:67024-011-08	3452 L in 1 CYLINDER		
NDC:67024-011-09	2697 L in 1 CYLINDER		
NDC:67024-011-10	1699 L in 1 CYLINDER		
NDC:67024-011-11	7100 L in 1 CYLINDER		
NDC:67024-011-12	9500 L in 1 CYLINDER		
NDC:67024-011-13	3113 L in 1 CYLINDER		
NDC:67024-011-14	31 L in 1 DEWAR		
NDC:67024-011-15	41 L in 1 DEWAR		
NDC:67024-011-16	45 L in 1 DEWAR		
NDC:67024-011-17	160 L in 1 DEWAR		
NDC:67024-011-18	180 L in 1 DEWAR		
NDC:67024-011-19	410 L in 1 DEWAR		
	NDC:67024-011-02 NDC:67024-011-03 NDC:67024-011-04 NDC:67024-011-05 NDC:67024-011-06 NDC:67024-011-07 NDC:67024-011-08 NDC:67024-011-09 NDC:67024-011-10 NDC:67024-011-11 NDC:67024-011-12 NDC:67024-011-13 NDC:67024-011-14 NDC:67024-011-15	NDC:67024-011-02 NDC:67024-011-03 650 L in 1 CYLINDER NDC:67024-011-04 248 L in 1 CYLINDER NDC:67024-011-05 165 L in 1 CYLINDER NDC:67024-011-06 170 L in 1 CYLINDER NDC:67024-011-07 198 L in 1 CYLINDER NDC:67024-011-08 3452 L in 1 CYLINDER NDC:67024-011-09 2697 L in 1 CYLINDER NDC:67024-011-10 1699 L in 1 CYLINDER NDC:67024-011-11 7100 L in 1 CYLINDER NDC:67024-011-12 9500 L in 1 CYLINDER NDC:67024-011-13 3113 L in 1 CYLINDER NDC:67024-011-14 31 L in 1 DEWAR NDC:67024-011-15 41 L in 1 DEWAR NDC:67024-011-16 45 L in 1 DEWAR NDC:67024-011-17 160 L in 1 DEWAR NDC:67024-011-18 180 L in 1 DEWAR	NDC:67024-011-02

Marketing Information					
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date		
NADA	NADA141354	03/08/2002			

Labeler - The Service Center LLC (943157438)

Establishment				
Name	Address	ID/FEI	Business Operations	
The Service Center LLC		943157438	manufacture	

Establishment				
Name	Address	ID/FEI	Business Operations	
The Service Center LLC		961683567	manufacture	

Establishment				
Name	Address	ID/FEI	Business Operations	
The Service Center LLC		961683575	manufacture	

Revised: 10/2015 The Service Center LLC