

**OXYGEN - oxygen gas**  
**Abbott Welding Supply**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click [here](#).*

-----

**Oxygen Compressed Label**

Oxygen, compressed usp

Oxygen 2

UN1072

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other applications Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Warning: High Pressure Oxidizing Gas.

Vigorously accelerates combustion.

Keep oil and grease away.

Open valve slowly.

Store and use with adequate ventilation.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

Use a back flow preventive device in the piping.

Close valve after each use and when empty.

Cylinder temperature should not exceed 52 degrees Celsius (125 degrees Fahrenheit).

Use in accordance with the material safety data sheet(MSDS).

**Net Contents**

Cylinder Type	Liters
T	9500
J	6900
D,E,Y	3470
XL	1970
E	690
D	420
C	210
B	150
A	95

CAS:7782-44-7

Do not remove this product label.

Abbott Welding Supply Co., Inc.

509 North First St. Olean, N.Y. 14760

(716)372-4265

**OXYGEN,  
COMPRESSED  
USP**

UN1072



**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING: HIGH PRESSURE OXIDIZING GAS.  
VIGOROUSLY ACCELERATES COMBUSTION.**

Keep oil and grease away.  
Open valve slowly.  
Store and use with adequate ventilation.  
Use only with equipment cleaned for oxygen service and rated for cylinder pressure.  
Use a back flow preventive device in the piping.  
Close valve after each use and when empty.  
Cylinder temperature should not exceed 52°C (125°F).  
Use in accordance with the Material Safety Data Sheet (MSDS).

**NET CONTENTS**

CYLINDER TYPE	LITERS
T .....	9500 <input type="checkbox"/>
J .....	6900 <input type="checkbox"/>
D,E,Y .....	3470 <input type="checkbox"/>
XL .....	1970 <input type="checkbox"/>
E .....	690 <input type="checkbox"/>
D .....	420 <input type="checkbox"/>
C .....	210 <input type="checkbox"/>
B .....	150 <input type="checkbox"/>
A .....	95 <input type="checkbox"/>

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**ABBOTT WELDING SUPPLY CO., INC.**

509 NORTH FIRST ST.

OLEAN, N.Y. 14760

(718) 372-4265

49335

12/1/04

49335 (08/04)

Oxygen, Refrigerated Liquid  
USP

Oxygen 2

UN1073

Always keep container in upright position.

Do not change or force fit connections.

Contents:        ltrs.    cu ft.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other applications Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Warning: Extremely cold oxidizing liquid and gas under pressure.

Vigorously accelerates combustion.

Combustibles in contact with liquid oxygen may explode on ignition or impact

Can cause severe frostbite.

Keep oil, grease and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52 degrees Celsius (125 degrees Fahrenheit).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the material safety data sheet(MSDS).

First Aid: In case of frostbite, obtain medical treatment immediately.

CAS:7782-44-7

Do not remove this product label.

Abbott Welding Supply Co., Inc.

509 North First St. Olean, N.Y. 14760

(716)372-4265

# REFRIGERATED LIQUID

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP**



**UN1073**

**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑**  
**DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: \_\_\_\_\_ LTRS:   
CU FT:

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**  
Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

**Produced by Air Liquefaction.**

**WARNING:** EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT CAN CAUSE SEVERE FROSTBITE.  
Keep oil, grease, and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin, or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Cylinder temperature should not exceed 52°C (125°F)  
Close valve after each use and when empty.  
Use a back flow preventive device in the piping.  
Use in accordance with the **Material Safety Data Sheet (MSDS)**.

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7782-44-7  
**DO NOT REMOVE THIS PRODUCT LABEL.**

**ABBOTT WELDING SUPPLY CO., INC**  
509 NORTH FIRST ST. OLEAN, N. Y. 14760  
(716) 372-4265

47136  
(R 10/05)

47136 (R 10/05)

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:49317-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

**Packaging**

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:49317-001-01	95 L in 1 CYLINDER		
2	NDC:49317-001-02	150 L in 1 CYLINDER		
3	NDC:49317-001-03	210 L in 1 CYLINDER		
4	NDC:49317-001-04	420 L in 1 CYLINDER		
5	NDC:49317-001-05	690 L in 1 CYLINDER		
6	NDC:49317-001-06	1970 L in 1 CYLINDER		
7	NDC:49317-001-07	3470 L in 1 CYLINDER		
8	NDC:49317-001-08	6900 L in 1 CYLINDER		
9	NDC:49317-001-09	9500 L in 1 CYLINDER		
10	NDC:49317-001-10	12696 L in 1 DEWAR		
11	NDC:49317-001-11	18925 L in 1 DEWAR		
12	NDC:49317-001-12	22211 L in 1 DEWAR		
13	NDC:49317-001-13	28572 L in 1 DEWAR		
14	NDC:49317-001-14	118283 L in 1 DEWAR		
15	NDC:49317-001-15	121621 L in 1 DEWAR		

**Marketing Information**

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		01/01/1980	

**Labeler** - Abbott Welding Supply (002125581)**Establishment**

Name	Address	ID/FEI	Business Operations
Abbott Welding Supply		002125581	manufacture

Revised: 8/2011

Abbott Welding Supply