

**OXYGEN- oxygen gas**  
**ADF Welding & Medical, Inc.**

-----  
**Oxygen**

**Oxygen Shoulder Label**


**OXYGEN, COMPRESSED USP UN 1072 OXYGEN 2 (R-K14A)**


**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS: LTRS \_\_ CU.FT. \_\_

**ADF WELDING & MEDICAL, INC.**

312 DODD BOULEVARD SE • ROME, GA 30161 • 706-295-5772





## Oxygen Body Label

### ADF WELDING & MEDICAL, INC

312 Dodd Blvd. S.E. Rome, GA 30161

706-295-5772

### OXYGEN, COMPRESSED UN 1072

#### DO NOT REMOVE THIS LABEL

Pressure: PSIG at 70°F

Size

Contents: Liters

### OXYGEN2

### OXYGEN\* U.S.P.

**WARNING:** HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. User shall secure cylinder in use and in storage. Use in upright position. Close valve after each use. Keep valve protective cap in place when not in use, if so equipped. Use in accordance of MSDS.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications.

**CAUTION:** Federal law prohibits dispensing without a prescription, Rx only.

**WARNING:** Uninterrupted use of high concentration of oxygen for more than 5 hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless in conjunction with resuscitative equipment. Keep Out of Reach of Children. Do not use or store near heat or open flame. CAS 7782-44-7 \*PRODUCED BY AIR LIQUEFACTION  
RETURN WITH 25 PSIG

# ADF WELDING & MEDICAL, INC.

312 Dodd Blvd. S. E. Rome, GA 30161

706-295-5772

## OXYGEN, COMPRESSED

UN 1072

DO NOT REMOVE THIS LABEL

Pressure: PSIG at 70° F,  
Size  
Contents liters



### OXYGEN\* U.S.P.

**WARNING:** HIGH PRESSURE OXIDIZING GAS.  
VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. User shall secure cylinder in use and in storage. Use in upright position. Close valve after each use. Keep valve protective cap in place when not in use. If so equipped, use in accordance with MSDS.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications,

**CAUTION:** Federal law prohibits dispensing without a prescription & only.

**WARNING:** Uninterrupted use of high concentrations of oxygen for more than 5 hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep Out of Reach of Children. Do not use or store near heat or open flame.  
CAS 7782-44-7 \*PRODUCED BY AIR LIQUEFACTION RETURN WITH 25 PSIG.

# ADF WELDING & MEDICAL, INC.

312 Dodd Blvd. S. E. Rome, GA 30161

706-295-5772

## OXYGEN, COMPRESSED

UN 1072

DO NOT REMOVE THIS LABEL

Pressure: PSIG at 70° F,  
Size  
Contents liters



### OXYGEN\* U.S.P.

**WARNING:** HIGH PRESSURE OXIDIZING GAS.  
VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. User shall secure cylinder in use and in storage. Use in upright position. Close valve after each use. Keep valve protective cap in place when not in use. If so equipped, use in accordance with MSDS.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications,

**CAUTION:** Federal law prohibits dispensing without a prescription & only.

**WARNING:** Uninterrupted use of high concentrations of oxygen for more than 5 hours may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep Out of Reach of Children. Do not use or store near heat or open flame.  
CAS 7782-44-7 \*PRODUCED BY AIR LIQUEFACTION RETURN WITH 25 PSIG.

## Oxygen Refrigerated

### OXYGEN

### REFRIGERATED LIQUID, U.S.P.

UN 1073

(CRYOGENIC LIQUID) Produced by Air Liquefaction

OXYGEN 2

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION**

### WARNING

EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications

**RX only.**

**WARNING!** Uninterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Use in accordance with Material Safety Data Sheet.

**WARNING:** Caution Federal Law Prohibits Dispensing without Prescription  
**FIRST AID**

IN CASE OF FROSTBITE, obtain medical treatment immediately.

PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.

**DO NOT REMOVE THIS PRODUCT LABEL**

**OXYGEN**  
REFRIGERATED LIQUID, U.S.P.  
**UN 1073**  
(CRYOGENIC LIQUID)

Produced by Air Liquefaction



**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

<p><b>WARNING</b></p> <p><b>WARNING!</b> EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.</p> <p>For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX only.</p> <p><b>WARNING!</b> Uninterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Use in accordance with Material Safety Data Sheet.</p> <p><b>WARNING:</b> Caution Federal Law Prohibits Dispensing without Prescription.</p>	<p><b>FIRST AID</b></p> <p><b>IN CASE OF FROSTBITE, obtain medical treatment immediately.</b></p> <p><b>PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.</b></p> <p>Company Name: Lot Number: Contents: Expiration Date:</p>
--	--

**DO NOT REMOVE THIS PRODUCT LABEL**

# OXYGEN

## REFRIGERATED LIQUID, U.S.P.

### UN 1073

(CRYOGENIC LIQUID)

Produced by Air Liquefaction



**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

**WARNING**

**WARNING!** EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX only.

**WARNING:** Caution Federal Law Prohibits Dispensing without Prescription.

**WARNING!** Uninterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Use in accordance with Material Safety Data Sheet.

**FIRST AID**

**IN CASE OF FROSTBITE, obtain medical treatment immediately.**

**PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.**

Company Name:  
Lot Number:  
Contents:  
Expiration Date:

**DO NOT REMOVE THIS PRODUCT LABEL**

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:64922-233
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
<b>Oxygen</b> (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	99 L in 100 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:64922-233-01	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
2	NDC:64922-233-02	256 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	

<b>3</b>	NDC:64922-233-03	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
<b>4</b>	NDC:64922-233-04	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
<b>5</b>	NDC:64922-233-05	1698 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
<b>6</b>	NDC:64922-233-06	2549 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
<b>7</b>	NDC:64922-233-08	3450 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
<b>8</b>	NDC:64922-233-09	6900 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
<b>9</b>	NDC:64922-233-10	160 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1990	
<b>10</b>	NDC:64922-233-11	180 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1990	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1990	

**Labeler** - ADF Welding & Medical, Inc. (609900782)

**Registrant** - ADF Welding & Medical, Inc. (609900782)

## Establishment

Name	Address	ID/FEI	Business Operations
ADF Welding & Medical, Inc.		609900782	manufacture(64922-233)

Revised: 10/2024

ADF Welding & Medical, Inc.