

OXYGEN- oxygen gas
Welders Supply Company

Oxygen

REFRIGERATED LIQUID OXYGEN USP LABEL

WELDERS SUPPLY COMPANY

111 BARRET PLACE • BELOIT, WI 53511

608-365-8825

OXYGEN,

REFRIGERATED LIQUID

UN 1073

OXYGEN, *U.S.P.

CAS: 7782-44-7

OXYGEN 2 45306 (05/15)

Gross Wt. **lbs.** **oz.**

Net Wt. **lbs.** **oz.**

Size

Contents

Liters

Rx ONLY. WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBELS IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.

Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID FIRST AID: IF ON SKIN: Thaw affected parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

TO BE REFILLED BY WELDERS SUPPLY COMPANY

DO NOT REMOVE THIS PRODUCT LABEL

WELDERS SUPPLY COMPANY
111 BARRET PLACE • BELOIT, WI 53511
608-365-8825

**OXYGEN,
REFRIGERATED LIQUID**

UN1073

OXYGEN, * U.S.P.

CAS: 7782-44-7



Gross Wt.	lbs.	oz.
Net Wt.	lbs.	oz.
Size		

Contents

Liters

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the *Federal Food, Drug and Cosmetic Act.*

***Produced by Air Liquefaction.**

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet



(SDS) before use.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**TO BE REFILLED BY WELDERS SUPPLY COMPANY
DO NOT REMOVE THIS PRODUCT LABEL**

HP OXYGEN USP SHOULDER LABEL

OXYGEN, COMPRESSED USP UN 1072

15060 (12/14) **OXYGEN 2**

OXYGEN, *U.S.P.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act **CAS 7782-44-7** RETURN WITH 25 PSIG

DO NOT REMOVE THIS PRODUCT LABEL

***Produced by Air Liquefaction**

WELDERS SUPPLY COMPANY

111 BARRET PLACE • BELOIT, WI 53511

1/800-236-8825

Pressure: PSIG at 70°F

Size

Contents liters



HP OXYGEN USP LABEL

OXYGEN, COMPRESSED USP

UN 1072

OXYGEN2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. PRODUCED BY AIR LIQUEFACTION

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7

DO NOT REMOVE THIS LABEL

Pressure:	Size	Contents:
2015 PSIG at 70°F	liters	

WELDERS SUPPLY COMPANY

111 BARRET PLACE • BELOIT, WI 53511

1/800-236-8825

OXYGEN, COMPRESSED USP UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction.**

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

Pressure:

Size

Contents

2015 PSIG at 70°F.

liters

WELDERS SUPPLY COMPANY

111 BARRET PLACE • BELOIT, WISCONSIN 53511

800-236-8825

41512
(12/14)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:11999-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	992 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:11999-001-01	90 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
2	NDC:11999-001-02	141 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
3	NDC:11999-001-03	198 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
4	NDC:11999-001-04	234 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
5	NDC:11999-001-05	387 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
6	NDC:11999-001-06	547 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
7	NDC:11999-001-07	643 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
8	NDC:11999-001-08	3172 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
9	NDC:11999-001-09	3511 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
10	NDC:11999-001-10	7051 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
11	NDC:11999-001-11	9401 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
12	NDC:11999-001-12	30 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
13	NDC:11999-001-13	40 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
14	NDC:11999-001-14	147 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
15	NDC:11999-001-15	3346 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
16	NDC:11999-001-16	4206 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
17	NDC:11999-001-17	7278 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
18	NDC:11999-001-18	640 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
19	NDC:11999-001-19	3160 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	

20	NDC:11999-001-20	7060 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
21	NDC:11999-001-21	640 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
22	NDC:11999-001-22	170 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
23	NDC:11999-001-23	8515 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
24	NDC:11999-001-24	248.4 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1973	

Labeler - Welders Supply Company (066869488)

Registrant - Welders Supply Company (066869488)

Establishment

Name	Address	ID/FEI	Business Operations
Welders Supply Company		066869488	manufacture(11999-001)

Revised: 11/2023

Welders Supply Company