

OXYGEN - oxygen gas
Terjan Co., Inc. DBA Valley Welding Supply Company

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

oxygen

OXYGEN,
COMPRESSED
USP

U.N. 1072

OXYGEN 2

17055 (R 04/35)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX ONLY.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. **PRODUCED BY AIR LIQUEFACTION. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.** Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Data Safety Sheet (MSDS).

CAS 7782-44-7

DO NOT REMOVE THIS LABEL

Valley Welding and Industrial Supply
6940 Meany Ave. Bakersfield, CA 93308

Contents: LTRS:

CU.FT

**OXYGEN,
COMPRESSED
USP**

UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. **PRODUCED BY AIR LIQUEFACTION. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.** Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the Material Safety Sheet (MSDS). **DO NOT REMOVE THIS PRODUCT LABEL.**

CONTENTS:
LTRS. L.
CU.FT



Valley Welding & Industrial Supply
6940 Meany Ave • Bakersfield, CA 93308

REFRIGERATED LIQUID
OXYGEN,
Refrigerated
Liquid
USP
UN 1073
OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: CU FT:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx ONLY.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.
VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52 degrees C (125 degrees F).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Data Safety Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

Valley Welding and Industrial Supply

6940 Meany Ave. Bakersfield, CA 93308

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**



UN1073

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↓
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS:
 CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.


Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7782-44-7. DO NOT REMOVE THIS PRODUCT LABEL.



OXYGEN
oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:42924-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42924-001-01	169 L in 1 CAN		
2	NDC:42924-001-02	254 L in 1 CYLINDER		
3	NDC:42924-001-03	396 L in 1 CYLINDER		
4	NDC:42924-001-04	622 L in 1 CYLINDER		
5	NDC:42924-001-05	679 L in 1 CYLINDER		
6	NDC:42924-001-06	2605 L in 1 CYLINDER		
7	NDC:42924-001-07	3539 L in 1 CYLINDER		
8	NDC:42924-001-08	4389 L in 1 CYLINDER		
9	NDC:42924-001-09	7050 L in 1 CYLINDER		
10	NDC:42924-001-10	9542 L in 1 CYLINDER		
11	NDC:42924-001-11	137138 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		02/18/2009	

Labeler - Terjan Co., Inc. DBA Valley Welding Supply Company (113799683)

Establishment

Name	Address	ID/FEI	Business Operations
Valley Welding Supply Company		113799683	manufacture

Revised: 3/2010

Terjan Co., Inc. DBA Valley Welding Supply Company