

**OXYGEN - oxygen gas**  
**Lake Welding Supply Company**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.*

-----  
**oxygen**

OXYGEN, Compressed U.S.P. UN1072      OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for use with oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 C (125F). Use in accordance with Material Safety Data Sheet (MSDS).

NET CONTENTS


CYLINDER TYPE      LITERS

T	9310
K	6900
D,E,Y	3500
Q	2320
XL	1970
AN-E	625
AN-D	360
R	570

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

LAKE WELDING SUPPLY CO. 363 Ottawa St. Muskegon, MI 49442 Phone: 231-722-3773  
47033 (R 05/06)



**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other applications, **R<sub>1</sub>** only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquetraction.

**WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.**

Keep oil and grease away.  
 Open valve slowly, adequate ventilation.  
 Store and use with equipment cleaned for oxygen service and rated for cylinder pressure.  
 Use a back flow preventive device in the piping.  
 Close valve after each use and when empty.  
 Cylinder temperature should not exceed 52°C (125°F).  
 Use in accordance with the Material Safety Data Sheet (MSDS).

NET CONTENTS	
CYLINDER TYPE	LITERS
T	9310
K	6900
S	4250
D/E/Y	3500
Q	2320
XL	1970
AN-E	625
AN-D	360
R	570

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**  
**LAKE WELDING SUPPLY CO.**  
 363 Ottawa St. • Muskegon, MI 49442  
 Phone: 231-722-3773

42033  
 (R 05/05)

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:10641-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10641-001-01	9310 L in 1 CYLINDER		
2	NDC:10641-001-02	6900 L in 1 CYLINDER		
3	NDC:10641-001-03	3500 L in 1 CYLINDER		
4	NDC:10641-001-04	2320 L in 1 CYLINDER		
5	NDC:10641-001-05	1970 L in 1 CYLINDER		
6	NDC:10641-001-06	625 L in 1 CYLINDER		
7	NDC:10641-001-07	360 L in 1 CYLINDER		
8	NDC:10641-001-08	570 L in 1 CYLINDER		

### Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		09/08/1953	

---

**Labeler** - Lake Welding Supply Company (017269580)

**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Lake Welding Supply Company		017269580	manufacture

Revised: 6/2010

Lake Welding Supply Company