


OXYGEN- oxygen gas

Ascension Via Christi Home Medical Wichita, LLC

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen, USP

Principal for Oxygen Product



OXYGEN

COMPRESSED

USP

UN 1072

Ascension Via Christi Home Medical Wichita, LLC

555 S. Washington

Wichita, KS 67211

1-800-452-5260

PRODUCED BY AIR LIQUIFICATION

WARNING: HIGH PRESSURE OXIDIZING GAS, VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Caution: Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen

content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

CAUTION: Keep oil and grease away. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Open valve slowly. Close valve after each use and when empty.

USE IN ACCORDANCE WITH MATERIAL SAFETY DATA SHEET.

DO NOT REMOVE THIS PRODUCT LABEL.


SIZE CONTENTS SIZE CONTENTS

___ "E" 682 Liters ___ "M-6" 165 Liters

___ "D" 415 Liters ___ "K" 6900 Liters

___ "C" 248 Liters ___ Other _____ Liters

**OXYGEN,
REFRIGERATED
LIQUID
USP**
UN 1073



CONTENTS: _____ LITERS

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING: DO NOT CHANGE OR FORCE FIT CONNECTIONS.
EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE
VIGOROUSLY ACCELERATES COMBUSTION.
NO FLAMING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT.
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE OR IGNITION OR INHALE.
CAN CAUSE SEVERE FROSTBITE.
Keep oil, grease, and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for customer movement.
Avoid spills. Do not walk on or roll equipment over spills.
Container temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.
Use a back flow preventive device in the system.
Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

ADMINING: For emergency use only when administered by properly trained personnel for oxygen deficiency and reventilation. For all other medical applications, see USP.
Unintentional use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.
Produced by Air Liquatex
DO NOT REMOVE THIS PRODUCT LABEL.

Ascension Via Christi Home Medical
865 S. Washington Suite 101
Wichita, KS 67211

CAS NO: 7782-44-7

**OXYGEN,
REFRIGERATED**

LIQUID USP

UN 1073

CONTENTS _____ LITERS

CAS NO: 7782-44-7

DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS
KEEP CONTAINER IN UPRIGHT POSITION. DO NOT
CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY
FIRE; OXIDIZER, CONTAINS REFRIGERATED GAS: MAY CAUSE
CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH
LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.
Do not get in eyes, on skin, or on clothing.Keep reduction valves free
from grease and oil. In case of fire, stop leak if safe to do so. Avoid
spills. Do not walk or roll equipment over spills. Store and use in a well
ventilated place.Use only with equipment of compatible materials
of construction and rated for cylinder pressure.Wear cold insulating
gloves/face shield/eye protection.Protect from sunlight when ambient
temperature exceeds 52 °C/125 °F.Container temperature should
not exceed 52 °C/125 °F. Close valve after each use and when
empty. Use a back flow preventative device in the piping. Do not
handle until all safety precautions have been read and understood.
Use only with equipment cleaned for oxygen service. Keep/store away
from combustible materials. Do not drop. Use suitable hand truck for
container movement.

FIRST AID:

IN CASE OF FROSTBITE:Thaw frosted parts with lukewarm water.
Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained
personnel for oxygen deficiency and resuscitation. For all other medical
applications, **Rx only**. Uninterrupted use of high concentrations of
oxygen over a long duration, without monitoring its effect on oxygen
content of arterial blood, may be harmful. Use only with pressure
reducing equipment and apparatus designed for oxygen. Do not
attempt to use on patients who have stopped breathing unless used in
conjunction with resuscitative equipment. Produced by Air Liquefaction.

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:59190-416(NDC:58356-001)
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:59190-416-00	248 L in 1 CYLINDER; Type 0: Not a Combination Product	05/15/2003	
2	NDC:59190-416-02	682 L in 1 CYLINDER; Type 0: Not a Combination Product	05/15/2003	
3	NDC:59190-416-07	39 L in 1 DEWAR; Type 0: Not a Combination Product	05/15/2003	
4	NDC:59190-416-08	450 L in 1 DEWAR; Type 0: Not a Combination Product	05/15/2003	
5	NDC:59190-416-05	19.49 L in 1 DEWAR; Type 0: Not a Combination Product	05/15/2003	
6	NDC:59190-416-06	29 L in 1 DEWAR; Type 0: Not a Combination Product	05/15/2003	
7	NDC:59190-416-12	10.34 L in 1 DEWAR; Type 0: Not a Combination Product	05/15/2003	
8	NDC:59190-416-11	623 L in 1 CYLINDER; Type 0: Not a Combination Product	05/15/2003	
9	NDC:59190-416-13	20.68 L in 1 DEWAR; Type 0: Not a Combination Product	05/15/2003	
10	NDC:59190-416-09	1699 L in 1 CYLINDER; Type 0: Not a Combination Product	05/15/2003	
11	NDC:59190-416-01	415 L in 1 CYLINDER; Type 0: Not a Combination Product	05/15/2003	
12	NDC:59190-416-03	6900 L in 1 CYLINDER; Type 0: Not a Combination Product	05/15/2003	
13	NDC:59190-416-04	165 L in 1 CYLINDER; Type 0: Not a Combination Product	05/15/2003	
14	NDC:59190-416-10	113 L in 1 CYLINDER; Type 0: Not a Combination Product	05/15/2003	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		05/15/2003	

Labeler - Ascension Via Christi Home Medical Wichita, LLC (181074626)

Registrant - Ascension Via Christi Home Medical Wichita, LLC (181074626)

Establishment

Name	Address	ID/FEI	Business Operations
Ascension Via Christi Home Medical Wchita, LLC		075169461	repack(59190-416)

Establishment

Name	Address	ID/FEI	Business Operations
Ascension Via Christi Home Medical Wchita, LLC		079479993	repack(59190-416)

Establishment

Name	Address	ID/FEI	Business Operations
Ascension Via Christi Home Medical Wchita, LLC		181074626	manufacture(59190-416)

Establishment

Name	Address	ID/FEI	Business Operations
Salina Regional Home Medical Services, LLC		832000827	repack(59190-416)

Establishment

Name	Address	ID/FEI	Business Operations
Ascension Via Christi Home Medical Wchita, LLC		152867326	repack(59190-416)

Revised: 12/2023

Ascension Via Christi Home Medical Wichita, LLC