

OXYGEN- oxygen gas
Temple Industrial Welding Supply Co

Oxygen

Refrigerated Liquid

Oxygen,
Refrigerated
Liquid

USP

UN1073

Oxygen, 2

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

Temple Welding Supply

2101 Industrial Blvd

Temple, TX 76704

254-778-5571

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID**

UN1073

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC
BURNS OR INJURY.
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY
EXPLODE ON IGNITION OR IMPACT.**

Do not handle until all safety precautions have been read and understood.
Keep and store away from clothing and other combustible materials.
Keep valves and fittings free from grease and oil.
Use and store only outdoors or in a well-ventilated place.
Wear cold insulating gloves, face shield, and eye protection.
In case of fire: Stop leak if safe to do so.
Use a back flow preventive device in the piping.
Use only with equipment of compatible materials of construction and rated for cylinder pressure.
Use only with equipment cleaned for oxygen service.
DO NOT change or force fit connections.
Avoid spills. Do not walk on or roll equipment over spills.
Close valve after each use and when empty.
Always keep container in upright position.
Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

Temple Welding Supply
2101 INDUSTRIAL BLVD
TEMPLE, TX 76704 • 254-778-5571

45131
(01/15)

OXYGEN

oxygen gas

Product Information

Product Type	PREScription ANIMAL DRUG	Item Code (Source)	NDC:11103-011
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:11103-011-12	132749 L in 1 DEWAR		
2	NDC:11103-011-13	142292 L in 1 DEWAR		
3	NDC:11103-011-14	153902 L in 1 DEWAR		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141387	01/01/2014	

Labeler - Temple Industrial Welding Supply Co (054381074)**Establishment**

Name	Address	ID/FEI	Business Operations
Temple Industrial Welding Supply Co		054381074	manufacture

Revised: 7/2020

Temple Industrial Welding Supply Co