

OXYGEN- oxygen gas
QUALITY AIR PRODUCTS INC

Oxygen

Oxygen, Compressed

UN1072

Do Not Remove This Product Label

Oxygen 2

Oxygen USP

Warning: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effects on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Warning: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperatures should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: 7782-44-7

PRODUCED BY AIR LIQUEFACTION

RETURN WITH 25 PSIG.

OX MH 6400 LITERS

OX E 705 LITERS

OX D 425 LITERS

OX MG 141 LITERS

OX CF



Refrigerated Liquid

Oxygen,
Refrigerated
Liquid
USP

UN1073

Oxygen, 2

Always keep container in upright position.
Do not change or force fit connections.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Warning: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS). First Aid: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

AIR SUPPLY

2829 Fort Worth Ave. Dallas, TX 75211
(214) 337-4761

REFRIGERATED LIQUID



**OXYGEN,
REFRIGERATED
LIQUID
USP**

UN1073

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING:

EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the **Material Safety Data Sheet (MSDS)**.

FIRST AID:

IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

AIR SUPPLY

2829 FORT WORTH AVE. • DALLAS, TX 75211
(214) 337-4761

41533
(R 10/04)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:63978-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:63978-001-01	141 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1980	
2	NDC:63978-001-02	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1980	
3	NDC:63978-001-03	705 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1980	
4	NDC:63978-001-04	6400 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1980	
5	NDC:63978-001-05	180 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1980	
6	NDC:63978-001-06	240 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1980	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205712	01/01/1980	

Labeler - QUALITY AIR PRODUCTS INC (557254711)

Establishment

Name	Address	ID/FEI	Business Operations
QUALITY AIR PRODUCTS INC		557254711	manufacture(63978-001)

Revised: 10/2023

QUALITY AIR PRODUCTS INC