

**OXYGEN - oxygen gas**  
**Nordan Smith Welding Supply**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, [click here](#).*

-----

**Oxygen Label**

OXYGEN, COMPRESSED USP  
UN1072

DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN 2

Medipure

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, RX only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing , unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE, OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: 7782-44-7

N/S NORDAN SMITH HATTIESBURG, MS.

17133 (R 05/05)



**OXYGEN,  
COMPRESSED  
USP**  
**UN1072**

DO NOT REMOVE THIS PRODUCT LABEL.



17133 (R 05/05)

Medipure

**WARNING:** For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**WARNING:** HIGH PRESSURE, OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleared for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the Material Safety Data Sheet (MSDS).

**NORDAN SMITH**  
HATTIESBURG, MS

Oxygen Refrigerated Liquid Label

Medipure

OXYGEN, REFRIGERATED LIQUID USP

UN1073

OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

CONTENTS: \_\_\_\_\_

LOT#: \_\_\_\_\_

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications. RX only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

N/S NORDAN SMITH HATTIESBURG, MS.

41033 (03/03)

Medipure™

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP**



**UN1073**

**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑**

CONTENTS: \_\_\_\_\_

LOT #: \_\_\_\_\_

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING:** EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.  
VIGOROUSLY ACCELERATES COMBUSTION.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT  
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin, or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Cylinder temperature should not exceed 52°C (125°F).  
Close valve after each use and when empty.  
Use in accordance with the **Material Safety Data Sheet (MSDS)**.

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**



**NORDAN SMITH**  
HATTIESBURG, MS

41033  
(03/03)

**OXYGEN**

oxygen gas

### Product Information

|                                |                          |                           |               |
|--------------------------------|--------------------------|---------------------------|---------------|
| <b>Product Type</b>            | HUMAN PRESCRIPTION DRUG  | <b>Item Code (Source)</b> | NDC:54416-001 |
| <b>Route of Administration</b> | RESPIRATORY (INHALATION) |                           |               |

### Active Ingredient/Active Moiety

| <b>Ingredient Name</b>                               | <b>Basis of Strength</b> | <b>Strength</b> |
|--|--------------------------|-----------------|
| Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065) | Oxygen                   | 995 mL in 1 L   |

### Packaging

| <b>#</b> | <b>Item Code</b> | <b>Package Description</b> | <b>Marketing Start Date</b> | <b>Marketing End Date</b> |
|----------|------------------|----------------------------|-----------------------------|---------------------------|
| 1        | NDC:54416-001-01 | 21 L in 1 DEWAR            |                             |                           |
| 2        | NDC:54416-001-02 | 41 L in 1 DEWAR            |                             |                           |
| 3        | NDC:54416-001-03 | 45 L in 1 DEWAR            |                             |                           |
| 4        | NDC:54416-001-04 | 180 L in 1 DEWAR           |                             |                           |
| 5        | NDC:54416-001-05 | 1133 L in 1 CYLINDER       |                             |                           |
| 6        | NDC:54416-001-06 | 1699 L in 1 CYLINDER       |                             |                           |
| 7        | NDC:54416-001-07 | 2263 L in 1 CYLINDER       |                             |                           |
| 8        | NDC:54416-001-08 | 3540 L in 1 CYLINDER       |                             |                           |
| 9        | NDC:54416-001-09 | 7109 L in 1 CYLINDER       |                             |                           |
| 10       | NDC:54416-001-10 | 8498 L in 1 CYLINDER       |                             |                           |
| 11       | NDC:54416-001-11 | 4361 L in 1 CYLINDER       |                             |                           |
| 12       | NDC:54416-001-12 | 396 L in 1 CYLINDER        |                             |                           |
| 13       | NDC:54416-001-13 | 651 L in 1 CYLINDER        |                             |                           |
| 14       | NDC:54416-001-14 | 164 L in 1 CYLINDER        |                             |                           |
| 15       | NDC:54416-001-15 | 170 L in 1 CYLINDER        |                             |                           |
| 16       | NDC:54416-001-16 | 113 L in 1 CYLINDER        |                             |                           |
| 17       | NDC:54416-001-17 | 196 L in 1 CYLINDER        |                             |                           |
| 18       | NDC:54416-001-18 | 255 L in 1 CYLINDER        |                             |                           |
| 19       | NDC:54416-001-19 | 640 L in 1 CYLINDER        |                             |                           |
| 20       | NDC:54416-001-20 | 396 L in 1 CYLINDER        |                             |                           |
| 21       | NDC:54416-001-21 | 50976 L in 1 CYLINDER      |                             |                           |

### Marketing Information

| <b>Marketing Category</b> | <b>Application Number or Monograph Citation</b> | <b>Marketing Start Date</b> | <b>Marketing End Date</b> |
|---------------------------|---|-----------------------------|---------------------------|
| unapproved medical gas    |   | 11/17/1993                  |                           |

**Labeler** - Nordan Smith Welding Supply (062456215)

### Establishment

| <b>Name</b> | <b>Address</b> | <b>ID/FEI</b> | <b>Business Operations</b> |
|-------------|----------------|---------------|----------------------------|
|-------------|----------------|---------------|----------------------------|

|                             |  |           |             |
|-----------------------------|--|-----------|-------------|
| Nordan Smith Welding Supply |  | 062187120 | manufacture |
|-----------------------------|--|-----------|-------------|

### Establishment

| Name                        | Address | ID/FEI    | Business Operations |
|-----------------------------|---------|-----------|---------------------|
| Nordan Smith Welding Supply |         | 187765938 | manufacture         |

### Establishment

| Name                        | Address | ID/FEI    | Business Operations |
|-----------------------------|---------|-----------|---------------------|
| Nordan Smith Welding Supply |         | 839309077 | manufacture         |

### Establishment

| Name                        | Address | ID/FEI    | Business Operations |
|-----------------------------|---------|-----------|---------------------|
| Nordan Smith Welding Supply |         | 021680079 | manufacture         |

### Establishment

| Name                        | Address | ID/FEI    | Business Operations |
|-----------------------------|---------|-----------|---------------------|
| Nordan Smith Welding Supply |         | 825560568 | manufacture         |

Revised: 12/2009

Nordan Smith Welding Supply