

**CARBON DIOXIDE- carbon dioxide gas**  
**MITCHELL WELDING SUPPLY DBA Meritus Texas**

-----  
**Carbon Dioxide**

CARBON DIOXIDE USP

UN1013

Rx Only. WARNING: Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9 DO NOT REMOVE THIS PRODUCT LABEL.

3539 Highway 271

Tyler, TX 75708


903-593-7343

[www.mitchellwelding.com](http://www.mitchellwelding.com)

MWS

Mitchell Welding Supply

CONTENTS: LTRS: CU.FT.



CARBON DIOXIDE

REFRIGERATED LIQUID USP

UN2187

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

Rx ONLY. Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. **WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE.** Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. **DO NOT** change or force fit connections.

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.

CAS: 124-38-9

FIRST AID

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

3539 Highway 271

Tyler, TX 75708

903-593-7343

MWS

Mitchell Welding Supply

www.mitchellwelding.com

DBG-COISP-MWY-PK25 2-10-25

# CARBON DIOXIDE REFRIGERATED LIQUID USP UN2187



**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

## WARNING

**Rx ONLY.** Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. **WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE.** Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. DO NOT change or force fit connections.

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.  
CAS: 124-38-9

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

**IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.



3539 Highway 271  
Tyler, TX 75708  
903-593-7343

**MWS**  
Mitchell Welding Supply  
www.mitchellwelding.com



**DO NOT REMOVE THIS PRODUCT LABEL**

PRINTED BY RATERMANN MFG., INC.  
www.rtmorder.com

CARBON DIOXIDE USP

UN1013

**WARNING: Rx ONLY.** Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

**WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE.** Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated

for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9

DO NOT REMOVE THIS PRODUCT LABEL.

3539 Highway 271

Tyler, TX 75708


903-593-7343

MWS

Mitchell Welding Supply

[www.mitchellwelding.com](http://www.mitchellwelding.com)

**CARBON DIOXIDE USP**





**UN1013**

**WARNING:** Rx ONLY. Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

**WARNING:** CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9  
DO NOT REMOVE THIS PRODUCT LABEL.

3539 Highway 271  
Tyler, TX 75708  
903-593-7343



[www.mitchellwelding.com](http://www.mitchellwelding.com)

CARBON DIOXIDE, REFRIGERATED LIQUID USP

UN2187

MWS

Mitchell Welding Supply

3539 Highway 271

Tyler, TX 75708

903-593-7343

www.mitchellwelding.com

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING:

USP Rx Only. Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.


WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. DO NOT change or force fit connections. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

CAS: 124-38-9



**CARBON DIOXIDE**

carbon dioxide gas

**Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:72276-004
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>CARBON DIOXIDE</b> (UNII: 142M471B3J) (CARBON DIOXIDE - UNII:142M471B3J)	CARBON DIOXIDE	990 mL in 1 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:72276-004-01	16055 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	
2	NDC:72276-004-02	18183 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	
3	NDC:72276-004-03	1745 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	
4	NDC:72276-004-04	14169 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	
5	NDC:72276-004-05	18609 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	

**Marketing Information**

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NDA	NDA220461	05/13/2025	

**Labeler** - MITCHELL WELDING SUPPLY DBA Meritus Texas (047833462)**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
MITCHELL WELDING SUPPLY DBA Meritus Texas		047833462	manufacture(72276-004)

**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Mitchell Welding Supply DBA Meritus Texas		118920889	manufacture(72276-004)

Revised: 3/2026

MITCHELL WELDING SUPPLY DBA Meritus Texas