

OXYGEN - oxygen gas
Corsicana Welding Supply, Inc.

Oxygen

Refrigerated Liquid
Oxygen,
Refrigerated
Liquid

UN1073
Oxygen, 2

Danger: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

First aid: If on skin: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

Corsicana Welding Supply
2151 E. Highway 31 Corsicana, TX 75109
903-872-7423

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID**

UN1073

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC
BURNS OR INJURY.
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY
EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood.
Keep and store away from clothing and other combustible materials.

Keep valves and fittings free from grease and oil.
Use and store only outdoors or in a well-ventilated place.
Wear cold insulating gloves, face shield, and eye protection.
In case of fire: Stop leak if safe to do so.

Use a back flow preventive device in the piping.
Use only with equipment of compatible materials of construction and rated for cylinder pressure.

Use only with equipment cleaned for oxygen service.
DO NOT change or force fit connections.
Avoid spills. Do not walk on or roll equipment over spills.
Close valve after each use and when empty.

Always keep container in upright position.
Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



Temple Welding Supply
2101 INDUSTRIAL BLVD
TEMPLE, TX 76704 • 254-778-5571

45131
(01/15)

OXYGEN			
oxygen gas			
Product Information			
Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:51500-011
Route of Administration	RESPIRATORY (INHALATION)		
Active Ingredient/Active Moiety			
	Ingredient Name	Basis of Strength	Strength
	OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L
Packaging			
#	Item Code	Package Description	Marketing Start Date
1	NDC:51500-011-12	132749 L in 1 DEWAR	
2	NDC:51500-011-13	142292 L in 1 DEWAR	
3	NDC:51500-011-14	153902 L in 1 DEWAR	
Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141387	01/01/2014	

Labeler - Corsicana Welding Supply, Inc. (557208170)

Establishment

Name	Address	ID/FEI	Business Operations
Corsicana Welding Supply, Inc.		557208170	manufacture

Revised: 7/2015

Corsicana Welding Supply, Inc.