OXYGEN- oxygen gas WAYNE OXYGEN AND WELDING SUPPLY COMPANY

oxygen

OXYGEN, COMPRESSED USP UN1072 PRODUCED BY AIR LIQUIFACTION OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical application, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL WAYNE OXYGEN AND WELDING SUPPLY CO, INC. 1100 EAST MARKET STREET CHARLOTTESVILLE, VA 22902 . 434-295-2334

CONTENTS: LTRS: CU. FT.



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2 CONTENTS: LTRS: CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be filled with oxygen USP only by establishments registered as a drug manufacturer

in accordance with the Federal Food, Drug, and Cosmetic Act. Produced by Air Liquiefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if sfe to do so. Use a back flow preventive device inthe piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or foll equipment over spills. Close valve after each use and when empty. Alway keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.


FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WAYNE OXYGEN AND WELDING SUPPLY CO, INC.

1100 EAST MARKET STREET

CHARLOTTESVILLE, VA 22902.434-295-2334



been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with tukewarm water.

Do not rub affected area. Get immediate medical

advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

WAYNE OXYGEN & WELDING SUPPLY CO, INC.

1100 EAST MARKET STREET,
CHARLOTTESVILLE, VA 22902 95-2334 4713

OXYGEN

oxygen gas

Product Information

Product Type PRESCRIPTION ANIMAL DRUG

Item Code (Source)

NDC:34940-011

Route of Administration RESPIRATORY (INHALATION)

Active Ingredient/Active Moiety

Treative ingredient retrie	greatend retive in total cy				
Ingredient Name	Basis of Strength	Strength			
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 L in 1 L			

Packaging						
#	Item Code	Package Description	Marketing Start Date	Marketing End Date		
1	NDC:34940-011-01	80 L in 1 DEWAR				
2	NDC:34940-011-02	180 L in 1 DEWAR				
3	NDC:34940-011-03	170 L in 1 CYLINDER				
4	NDC:34940-011-04	425 L in 1 CYLINDER				
5	NDC:34940-011-05	651 L in 1 CYLINDER				
6	NDC:34940-011-06	708 L in 1 CYLINDER				
7	NDC:34940-011-07	4417 L in 1 CYLINDER				
8	NDC:34940-011-08	7249 L in 1 CYLINDER				

Marketing Information						
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date			
NADA	NADA141396	11/08/2010				

Labeler - Wayne Oxygen and Welding Supply Company (024000275)

Establishment					
Name	Address	ID/FEI	Business Operations		
WAYNE OXYGEN AND WELDING SUPPLY COMPANY		165988841	manufacture		

Revised: 12/2015 WAYNE OXYGEN AND WELDING SUPPLY COMPANY