

OXYGEN- oxygen gas
Island Supply Welding Co Inc

oxygen

OXYGEN, COMPRESSED USP
UN1072
PRODUCED BY AIR LIQUEFACTION
OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical application, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect of oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINERS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.
ISLAND SUPPLY WELDING CO.
4920 W HWY 30
GRAND ISLAND, NE 68803
308-382-3680



REFRIGERATED LIQUID
OXYGEN, REFRIGERATED LIQUID USP
UN1073
OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.
WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect

on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSITY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty.

Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

ISLAND SUPPLY WELDING CO.

4920 W HWY 30

GRAND ISLAND, NE 68803

308-382-3680

DO NOT REMOVE THIS PRODUCT LABEL.



OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:21624-011
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:21624-011-11	179 L in 1 DEWAR		
2	NDC:21624-011-12	163 L in 1 DEWAR		
3	NDC:21624-011-13	148 L in 1 DEWAR		
4	NDC:21624-011-14	8636 L in 1 CYLINDER		
5	NDC:21624-011-15	6909 L in 1 CYLINDER		
6	NDC:21624-011-16	4260 L in 1 CYLINDER		
7	NDC:21624-011-17	3511 L in 1 CYLINDER		
8	NDC:21624-011-18	2350 L in 1 CYLINDER		
9	NDC:21624-011-19	659 L in 1 CYLINDER		
10	NDC:21624-011-20	396 L in 1 CYLINDER		
11	NDC:21624-011-21	248 L in 1 CYLINDER		
12	NDC:21624-011-22	164 L in 1 CYLINDER		
13	NDC:21624-011-23	75 L in 1 DEWAR		
14	NDC:21624-011-24	112 L in 1 CYLINDER		
15	NDC:21624-011-25	647 L in 1 CYLINDER		
16	NDC:21624-011-26	3455 L in 1 CYLINDER		
17	NDC:21624-011-27	699 L in 1 CYLINDER		
18	NDC:21624-011-28	2549 L in 1 CYLINDER		
19	NDC:21624-011-29	198 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141399	01/01/1950	

Labeler - Island Supply Welding Co Inc (035034974)

Establishment

Name	Address	ID/FEI	Business Operations
Island Supply Welding Co Inc		035034974	manufacture

Revised: 7/2020

Island Supply Welding Co Inc