

**OXYGEN - oxygen gas**  
**Eastern Medical Equipment**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.*

-----  
**Oxygen**

**Principal for Oxygen Product**

**OXYGEN,  
COMPRESSED  
USP**  
UN 1072

**C.A.S. NO. 7782-44-7**

Representative Labeling  
pursuant to 21 CFR 207.3 (10)  
Company name and contact information  
are printed in this box

**⚠ WARNING: HIGH PRESSURE, OXIDIZING GAS, VIGOROUSLY ACCELERATES COMBUSTION.  
NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT.**  
Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation.  
Use only with equipment cleaned for oxygen service and rated for cylinder pressure.  
Use a back flow preventative device in the piping.  
Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F).  
Use in accordance with Material Safety Data Sheet (MSDS).  
DO NOT REMOVE THIS PRODUCT LABEL.

**⚠ WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**Produced by Air Liquefaction.**

Size	Contents	Size	Contents
<input type="checkbox"/> "M6"	170 Liters	<input type="checkbox"/> "E"	682 Liters
<input type="checkbox"/> "C"	248 Liters	<input type="checkbox"/> "H"	6910 Liters
<input type="checkbox"/> "D"	415 Liters	<input type="checkbox"/> Other	____ Liters

03227002

LOT  
LITER

164.

**Representative Labeling pursuant  
to 21 CFR 207.3(10)**

OXYGEN, COMPRESSED USP  
UN 1072

C.A.S No. 7782-44-7

WARNING: HIGH PRESSURE, OXIDIZING GAS, VIGOROUSLY ACCELERATES  
COMBUSTION.

Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation.  
Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

Use a back flow preventative device in the piping.

Close valve after each use and when empty. Cylinder temperatures should not exceed 52°C (125°F).

Use in accordance with Material Safety Data Sheet (MSDS).

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING:

For emergency use only when administered by properly trained  
personnel for oxygen deficiency and resuscitation. For all other  
medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long  
duration, without monitoring its effect on oxygen content of arterial  
blood, may be harmful. Use only with pressure reducing equipment  
and apparatus designed for oxygen. Do not attempt to use on  
patients who have stopped breathing, unless used in conjunction  
with resuscitative equipment.

Produced by Air Liquefaction

## OXYGEN

oxygen gas

### Product Information

Product Type

HUMAN PRESCRIPTION DRUG

Item Code (Source)

NDC:53773-001

<b>Route of Administration</b>	RESPIRATORY (INHALATION)
--------------------------------	--------------------------

<b>Active Ingredient/Active Moiety</b>		
<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	99 L in 100 L

<b>Packaging</b>				
<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:53773-001-01	680 L in 1 CYLINDER		
2	NDC:53773-001-02	425 L in 1 CYLINDER		
3	NDC:53773-001-03	113 L in 1 CYLINDER		
4	NDC:53773-001-04	3540 L in 1 CYLINDER		
5	NDC:53773-001-05	6400 L in 1 CYLINDER		

<b>Marketing Information</b>			
<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
unapproved medical gas		01/01/1936	

**Labeler** - Eastern Medical Equipment (626622562)