

OXYGEN- oxygen gas
NLR Welding Supply, Inc.

OXYGEN COMPRESSED LABEL

OXYGEN, COMPRESSED USP UN 1072

NLR WELDING SUPPLY, INC.


5001 E. Broadway N.L.R., AR 72117

(501) 945-0986 www.nlrwelding.com NLR-01

OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL



OXYGEN REFRIGERATED LIQUID

Oxygen, Refrigerated Liquid, USP UN1073

Rx ONLY

NLR NLR WELDING SUPPLY, INC.

5001 E. Broadway N.L.R., AR 72117

(501) 945-0986 www.nlrwelding.com NLR-01

OXYGEN 2 LOT# NET CONTENTS: NLR-101

Rx ONLY. WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment. **Produced by Air Liquefaction.**

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID FIRST AID: IF ON SKIN:** Thaw affected parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL



OXYGEN

oxygen gas

| Product Information | | | | |
|--|--|---|----------------------|--------------------|
| Product Type | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:62045-4333 | |
| Route of Administration | RESPIRATORY (INHALATION) | | | |
| Active Ingredient/Active Moiety | | | | |
| Ingredient Name | | Basis of Strength | Strength | |
| OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | | OXYGEN | 99 L in 100 L | |
| Packaging | | | | |
| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
| 1 | NDC:62045-4333-2 | 282 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1986 | |
| 2 | NDC:62045-4333-1 | 623 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1986 | |
| 3 | NDC:62045-4333-0 | 340 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1986 | |
| 4 | NDC:62045-4333-3 | 1275 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1986 | |
| Marketing Information | | | | |
| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date | |
| NDA | NDA205865 | 01/01/1986 | | |

Labeler - NLR Welding Supply, Inc. (144730421)

Registrant - Nlr Welding Supply, Inc. (144730421)

Establishment

| Name | Address | ID/FEI | Business Operations |
|--------------------------|---------|-----------|-------------------------|
| Nlr Welding Supply, Inc. | | 144730421 | manufacture(62045-4333) |

Revised: 11/2023

NLR Welding Supply, Inc.