OXYGEN- oxygen gas Gas and Supply

Oxygen

OXYGEN, COMPRESSED USP US1072 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7. DO NOT REMOVE THIS PRODUCT LABEL CONTENTS: LTRS: CU.FT. GAS AND SUPPLY **5000 SAUNDERS ROAD**

FORT WORTH, TX 76119 817-478-6004 GCS-0XYUSP-GS03-PK500 6/29/15 WARNING: For emergency use only when administered by properly trained p For all other medical applications, **Rx only**. Uninterrupted use of high concent manifering in the second s rmful. Do nol a monitoring its effect on oxygen content of affects blood, may be harmful. Do not affect breathing unless used in conjunction with resuscitative equipment. Produced by Nr INTERIENCY CIDE, OVERSED, CONTAINE CAS LINNER PRESSURE, MAY EXPLO-INTERNSIP FIRE OXIDIZER. CONTAINS GAS UNDER PRESSURE was trem clothing Prezadions have been read and understood. Keep and store area into notions to it under and tensor to it. view usern read and understood, keep and some only outdoors or in Valves and fittings free from grease and oil. Use and store only outdoors in least least it was leak if sale to do so. Use a back flow preventive device in the printing Use of If construction and acted for our preventive device in the printing Use of ment clear sow in some to do so. Use a back low preventive device in use years, of construction and railed for cylinder pressure. Use only with equipment of slowly. Close valve after each use and when empty. Protect from sublight when an P. Read and follow the Code, back Code (COC) (COC DO NOT REMOVE THIS PRI 5000 SAUNDERS ROAD wurny: wuose valve after each use and when empty. Process using away?" 125 FJ, Read and follow the Safety Data Sheet (SDS) before use. CAS: TR2-44-7 FORT WORTH, TX 76119 817-478-6004

REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. CONTENTS: LTRS... CU.FT.

WARNING: USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSITY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL. GAS AND SUPPLY 5000 SAUNDERS ROAD FORT WORTH, TX 76119 817-478-6004

| REFRIGERATED LIQUID DXYGEN, Refrigerated Liquid JSP JN1073 | ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. 1 DO NOT CHANGE OR FORCE FIT CONNECTIONS. | LTRS: U | USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of a raterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. | MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURS OR INJURY. CUBIRS OR INJURY. CUBIRS OR INJURY. CUMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLORE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep avalves and fittings free from grasse and oil. Use and store only outdoors or in a well- ventilated place. Wear cold insulating gloves, face shield, and eventilated place. Wear cold insulating gloves, face shield, and wentilated place. Wear cold insulating gloves face shield, and eventilated place. Wear cold insulating gloves face shield, and eventilated place. Wear cold insulating gloves face shield, and eventilate place. Wear cold insulating the piping. Use only with equipment of compatible materials of construction and rated for cylinder present. Use only with equipment for spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. | IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. | CAS: 7782-44-7 Do not remove this product label. | FIT-478-6004 |
|---|---|-----------|--|--|---|---|---------------------|
| REFRI OXYGEN OXYGEN BREFRIGE LIQUID USP UN1073 | 1 ALWAY DO NO | CONTENTS: | WARNING | DANGER | FIRST AID: | 20 | |

| | roduct Infor | | | | |
|---|------------------------|--|---------------------------------------|-------------------------|-----------------------|
| Product Type Route of Administration | | | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:70101-001 |
| | | stration | RESPIRATORY (INHALATION) | | |
| | | | | | |
| Ac | tive Ingredi | | - | | |
| DXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | | | | Basis of Strength | 995 mL in 1 L |
| 0. | IGEN (UNII, 386 | 1114005) (UX | IGEN - UNII.3881114003) | OATGEN | 995 ML M I L |
| Pa | ckaging | | | | |
| # | ltem Code | Р | ackage Description | Marketing Start Date | Marketing End Date |
| 1 | NDC:70101- 001-01 | 180 L in 1 DE Product | WAR; Type 0: Not a Combination | 04/01/2013 | |
| 2 | NDC:70101- 001-02 | 200 L in 1 DE Product | WAR; Type 0: Not a Combination | 04/01/2013 | |
| 3 | NDC:70101- 001-03 | 198 L in 1 CY Product | 'LINDER; Type 0: Not a Combination | 04/01/2013 | |
| 4 | NDC:70101- 001-04 | 425 L in 1 CY Product | 'LINDER; Type 0: Not a Combination | 04/01/2013 | |
| 5 | NDC:70101- 001-05 | 708 L in 1 CY Product | 'LINDER; Type 0: Not a Combination | 04/01/2013 | |
| 6 | NDC:70101- 001-06 | 3228 L in 1 C Product | YLINDER; Type 0: Not a Combination | 04/01/2013 | |
| 7 | NDC:70101- 001-07 | 3540 L in 1 C Product | YLINDER; Type 0: Not a Combination | 04/01/2013 | |
| 8 | NDC:70101- 001-08 | 6456 L in 1 CYLINDER; Type 0: Not a Combination Product | | 04/01/2013 | |
| 9 | NDC:70101- 001-09 | 7108 L in 1 CYLINDER; Type 0: Not a Combination Product | | 04/01/2013 | |
| 10 | NDC:70101- 001-10 | 7249 L in 1 CYLINDER; Type 0: Not a Combination Product | | 04/01/2015 | |
| 11 | NDC:70101- 001-11 | 7957 L in 1 CYLINDER; Type 0: Not a Combination Product | | 04/01/2013 | |
| 12 | NDC:70101- 001-12 | Product | YLINDER; Type 0: Not a Combination | 04/01/2013 | |
| 13 | NDC:70101- 001-13 | 9543 L in 1 C Product | YLINDER; Type 0: Not a Combination | 04/01/2013 | |
| | | | | | |
| Μ | arketing | Informa | tion | | |
| | Marketing Category | Applica | ation Number or Monograph Citation | Marketing Start Date | Marketing End Date |
| ND | A | NDA20571 | 2 | 04/01/2013 | |

Labeler - Gas and Supply (088765203)

Establishment

| Name | Address | ID/FEI | Business Operations |
|----------------|---------|-----------|----------------------------|
| Gas and Supply | | 088765203 | manufacture(70101-001) |

Revised: 10/2023

Gas and Supply