

COMPRESSED GAS, OXIDIZING, N.O.S. - oxygen gas
Air Liquide Healthcare America Corporation

Compressed Gas, Oxidizing, N.O.S. (OXYGEN, HELIUM) Label

WARNING: DO NOT HANDLE CYLINDER OR USE CONTENTS UNTIL: 1) YOU HAVE READ AND UNDERSTAND THE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT. CALL 1-800-231-1366 FOR MORE COPIES. 2) YOU ARE TRAINED TO USE CYLINDER AND CONTENTS, INCLUDING EMERGENCY PROCEDURES.

COMPRESSED GAS, OXIDIZING, N.O.S. (OXYGEN, HELIUM) UN 3156

NON-FLAMMABLE 2 OXIDIZER 5.1

_____ % Oxygen USP _____ % Helium USP

Only for Oxygen contents above 23.5%

WARNING: HIGH PRESSURE, OXIDIZING GAS, VIGOROUSLY ACCELERATES COMBUSTION. Secure cylinder and provide adequate ventilation in storage and use. Keep oil and grease away. No smoking in cylinder area. Do not use or store near heat or open flame. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Cylinder temperatures should not exceed 125°F (52°C). Open valve slowly. Close valve after each use and when empty. Return with at least 25 PSIG pressure. Use in accordance with Material Safety Data Sheet and Compressed Gas Association Publication P-1.

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

CAUTION: USE NO OIL ON VALVE OR CONNECTIONS. TRANSFILLING OF THIS GAS IS PROHIBITED.

DO NOT REMOVE THIS PRODUCT LABEL.

AIR LIQUIDE HEALTHCARE AMERICA CORP.
P. O. BOX 460229
Houston, TX 77056

M73H-3 L10

**COMPRESSED
GAS, OXIDIZING,
N.O.S.
(Oxygen, Helium)
UN 3156**

WARNING: DO NOT HANDLE CYLINDER OR USE CONTENTS UNTIL: 1) YOU HAVE READ AND UNDERSTAND THE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT. CALL 1-800-231-1366 FOR MORE COPIES. 2) YOU ARE TRAINED TO USE CYLINDER AND CONTENTS, INCLUDING EMERGENCY PROCEDURES.





_____ % Oxygen USP _____ % Helium USP

Only for Oxygen content above 23.5%

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Secure cylinder and provide adequate ventilation in storage and use. Keep oil and grease away. No smoking in cylinder area. Do not use or store near heat or open flame. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Cylinder temperature should not exceed 125°F (52°C). Open valve slowly. Close valve after each use and when empty. **Return with at least 25 PSIG pressure.** Use in accordance with Material Safety Data Sheet and Compressed Gas Association Publication P-1.

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

CAUTION: USE NO OIL ON VALVE OR CONNECTIONS. TRANSFILLING OF THIS GAS IS PROHIBITED.

DO NOT REMOVE THIS PRODUCT LABEL.



AIR LIQUIDE HEALTHCARE AMERICA CORP.
P.O. BOX 460229
Houston, TX 77056

M73H-3
L10

COMPRESSED GAS, OXIDIZING, N.O.S.

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:64735-070
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	40 L in 100 L

Inactive Ingredients

Ingredient Name	Strength
HELIUM (UNII: 206GF3GB41)	

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:64735-070-04	708 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205712	01/01/1960	

Labeler - Air Liquide Healthcare America Corporation (087757167)

Registrant - Air Liquide Healthcare America Corporation (087757167)

Establishment

Name	Address	ID/FEI	Business Operations
Air Liquide Healthcare America Corporation		067631762	manufacture(64735-070)

Establishment

Name	Address	ID/FEI	Business Operations
Air Liquide Industrial U.S. LP		831995829	manufacture(64735-070)