

OXYGEN- oxygen gas
Major Medical Supply LLC

Oxygen

OXYGEN COMPRESSED USP Product Label

OXYGEN COMPRESSED USP UN 1072

OXYGEN-2

DANGER:

COMPRESSED, OXIDIZING GAS, MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

In case of fire: stop leak if safe to do so. Keep reduction valves free from grease and oil. Open valve slowly. Store and use in a well ventilated place. Use a back flow preventive device in the piping. Close valve after after each use and when empty. Protect from sunlight when ambient temperature exceeds 52° C/125° F. Container temperature should not exceed 52° C/125° F. Do not handle until all safety precautions have been read and understood. Keep/store away from combustible materials. Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patents who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction

Contents	Size
170 Liters	M6
248 Liters	C
415 Liters	D
682 Liters	E
6910 Liters	H
_____ Liters	Other

CAS NO: 7782-44-7

Major Medical Supply
1649 Main Street
Longmont, CO 80501
(303) 651-6400

OXYGEN, COMPRESSED USP

UN 1072

DANGER:

COMPRESSED, OXIDIZING GAS.
MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

In case of fire: stop leak if safe to do so. Keep reduction valves free from grease and oil. Open valve slowly. Store and use in a well ventilated place. Use a back flow preventative device in the piping. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C/125 °F. Container temperature should not exceed 52 °C/125°F. Do not handle until all safety precautions have been read and understood. Keep/store away from combustible materials. Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.



Contents	Size
170 Liters	<input type="checkbox"/> M6
248 Liters	<input type="checkbox"/> C
415 Liters	<input type="checkbox"/> D
682 Liters	<input type="checkbox"/> E
6910 Liters	<input type="checkbox"/> H
_____ Liters	<input type="checkbox"/> Other

CAS NO: 7782-44-7

Major Medical Supply
649 Main Street
Longmont, CO 80501
T: 303.651.6400 F: 303.678.4837

OXYGEN REFRIGERATED LIQUID USP Product Label

OXYGEN REFRIGERATED LIQUID USP UN 1073

OXYGEN 2

CONTENTS: _____ LITERS

CAS NO:7782-44-7

DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS REFRIGERATED GAS: MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get into eyes, on skin, or on clothing. Keep reduction valves free from grease and oil. In case of fire, stop leak if safe to do so. Avoid spills. Do not walk or roll equipment over spills. Store and use in a well ventilated place. use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52° C/125° F. Container temperature should not exceed 52° C/125° F. Close valve after each use and when empty. Use a back flow preventive device in the pipping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

FIRST AID:

IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advise/attention.

DO NOT REMOVE THIS PRODUCT LABEL

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

Major Medical Supply
1649 Main Street
Longmont, CO 80501
(303) 651-6400

**OXYGEN,
REFRIGERATED
LIQUID USP**

UN 1073



UN 1073



CONTENTS: _____ **LITERS**

CAS NO: 7782-44-7



DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free from grease and oil. In case of fire, stop leak if safe to do so. Avoid spills. Do not walk or roll equipment over spills. Store and use in a well ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52 °C/125 °F. Container temperature should not exceed 52 °C/125 °F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

FIRST AID:

IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure

content of arterial blood, may be harmful even if used with pressure-reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

Major Medical Supply

1649 Main Street
Longmont, CO 80501
(303) 651-6400

OXYGEN, REFRIGERATED LIQUID USP

UN 1073



CONTENTS: _____ **LITERS**

CAS NO: 7782-44-7

DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free

from grease and oil. In case of fire, stop leak if safe to do so. Avoid spills. Do not walk or roll equipment over spills. Store and use in a well ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52 °C/125 °F. Container temperature should not exceed 52 °C/125 °F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

FIRST AID:

IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

Major Medical Supply

1649 Main Street
Longmont, CO 80501
(303) 651-6400

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:65700-1649
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:65700-1649-1	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
2	NDC:65700-1649-2	248 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
3	NDC:65700-1649-3	415 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
4	NDC:65700-1649-4	682 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
5	NDC:65700-1649-5	6910 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
6	NDC:65700-1649-6	41 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/2000	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205849	01/01/2000	

Labeler - Major Medical Supply LLC (121414452)

Registrant - Major Medical Supply LLC (121414452)

Establishment

Name	Address	ID/FEI	Business Operations
Major Medical Supply LLC		121414452	manufacture(65700-1649)

Establishment

Name	Address	ID/FEI	Business Operations
Praxair, Inc.		102526084	manufacture(65700-1649)