

**OXYGEN - oxygen gas**  
**American Welding & Gas**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, [click here](#).*

-----  
**Liquid Oxygen Label**

OXYGEN,  
REFRIGERATED LIQUID  
USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: \_\_\_, CU FT: \_\_\_

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.  
VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR  
IMPACT CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52°C (125°F)

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

**REFRIGERATED LIQUID**

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP**

**UN1073**



**! ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. !**  
**DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: LTR:   
CUFT:

**WARNING:** For an agency and only when administered by a properly trained personnel for Oxygen Therapy and Respiration. For all other uses see 49 CFR 172.101, 172.102 & 172.103.  
Under normal use of high concentrations of oxygen over a long duration, without monitoring the flow oxygen content of ambient air, may be harmful. Use only with pressure reducing equipment and separate flowmeter for oxygen. Do not attempt to use on patients who have stopped breathing. Oxygen used in conjunction with two active electrodes.

**Produced by Air Liquide/Inco.**

**WARNING:** EXTREMELY COLD. DO NOT ALLOW LIQUID AND GAS UNDER PRESSURE.  
WARRANTY OF WORK: INCO/USP CO. MAINTAINS CONTACT TO US BY CONTACTING THE SALES OFFICE OR MAY EXERCISE ON BULK PURCHASES CONTACT OUR SALES OFFICE.  
Keep all gasses and cylinders in proper use only with equipment used for Oxygen service. Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin, or clothing.  
For best protection, wear face shield and gloves.  
Do not drink. Use suitable hand tools for cylinder movement.  
Accidents: Do not take any fire equipment into use until cylinder has been at least 15 minutes at 70°F (21°C).  
Clean valve after each use a 30 second delay.  
See a local Toxic Response Agency in the event that an accident with the **Welding Safety Data Sheet (MSDS)**.

**FIRST AID:** IN CASE OF FROSTBITE, call a medical professional. Remove clothing.  
DO NOT REMOVE THIS PRODUCT LABEL.

**inweld corp**  
3533 WEST SOUTHERN AVENUE  
INDIANAPOLIS, IN 46241  
(317) 248-0651

11/14  
19-0000

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:49778-005
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	992 L in 1000 L

### Packaging

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:49778-005-01	140 L in 1 DEWAR		

### Marketing Information

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
unapproved medical gas		05/01/2009	

**Labeler** - American Welding & Gas (035216530)

### Establishment

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
American Welding & Gas		013699083	manufacture

Revised: 6/2010

American Welding & Gas