NITROGEN - nitrogen gas Terjan Co., Inc. DBA Valley Welding Supply Company

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

nitrogen

REFRIGERATED LIQUID NITROGEN, REFRIGERATED LIQUID NF UN 1977

NON-FLAMMABEL GAS 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

DO NOT CHANGE OR FORCE FIT CONNECTIONS. RX only.

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken. WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE. CAN CAUSE RAPID SUFFOCATION. CAN CAUSE SEVERE FROSTBITE.

Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Cylinder temperature should not exceed 52 degrees C (125 degrees F). close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IF INHALED, remove to fresh air. If not breathin, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL VWS Valley Welding and Industrial Supply 6940 Meany Ave Bakersfield, CA 93308

NITROGEN,
REFRIGERATED
LIQUID

NF

ON NOT CHANGE OR FORCE FIT CONNECTIONS.
DO NOT CHANGE OR FORCE FIT CONNECTIONS.
CONTRINGERATED allowers who is experienced in the use and increase practitioner who is experienced in the use and increase practitioner, who is experienced in the use and administration, and write the hazards, contributions and effects, doesage, mathods, and requency and duration of effects and represent properties.

EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE. CAM CAUSE RAPID SUFFOCATION.
CAM CAUSE RAPID SUFFOCATION.
CAM CAUSE RAPID SUFFOCATION.
CAM CAUSE RAPID SUFFOCATION.
Use in accordance with the deserted subject of continuer movement. Defined interests shed and glorce.
FOR the deserted was refused and consect 22'O (125'F), Close who after each use and when empty.
Use in accordance with the deserted Safety and Safet (125'F), Close who after each use and when empty.
Use in accordance with the deserted Safety and Safet (125'F), Close who after each use and printing give artificial respiration. If the destrict Safety and Safet (125'F), Close who after each use and printing give artificial respiration.

If CAS: 7727-37-9
DO NOT REMOVE THIS PRODUCT LABEL.


CAS: 7727-37-9
BO NOT REMOVE THIS PRODUCT LABEL.

FLAMMABLE GAS 2

UN 1066

RX ONLY. WARNING: administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. CAUTION: HIGH PRESSURE GAS. CAN CAUSE RAPID SUFFOCATION. Store and use with adequate ventilation. Use equipment rated for cylinder pressure. Use a back flow preventative device in the piping. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS). FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. CAS: 7727-37-9 DO NOT REMOVE THIS PRODUCT LABEL CONTENTS: LITERS. CU. FT.

VWS Valley Welding and Industrial Supply 6940 Meany Ave. Bakersfield, CA 93308



NITROGEN

nitrogen gas

Product Information			
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:42924-002
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety		
Ingredient Name	Basis of Strength	Strength
Nitrogen (UNII: N762921K75) (Nitrogen - UNII:N762921K75)	Nitrogen	990 mL in 1 L

P	Packaging			
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42924-002-01	396 L in 1 CYLINDER		
2	NDC:42924-002-02	651 L in 1 CYLINDER		
3	NDC:42924-002-03	3256 L in 1 CYLINDER		
4	NDC:42924-002-04	6510 L in 1 CYLINDER		
5	NDC:42924-002-05	8516 L in 1 CYLINDER		

6 NDC:42924-002-06	106189 L in 1 CYLINDER			
7 NDC:42924-002-07	116 L in 1 CYLINDER			
N.C I Air or T C Air				
Marketing Information				
Marketing Category	Application Number or Monogra	ph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas			03/17/2010	

Labeler - Terjan Co., Inc. DBA Valley Welding Supply Company (113799683)

Establishment				
Name	Address	ID/FEI	Business Operations	
Valley Welding Supply Company		113799683	manufacture	

Revised: 4/2010 Terjan Co., Inc. DBA Valley Welding Supply Company