

OXYGEN- oxygen gas
CHV Home Medical Equipment Company, LLC

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen

Principal for Oxygen Product

OXYGEN, COMPRESSED USP
UN 1072

C.A.S No. 7782-44-7

WARNING: HIGH PRESSURE, OXIDIZING GAS, VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

Use a back flow preventative device in the piping.

Close valve after each use and when empty. Cylinder temperatures should not exceed 52°C (125°F).

Use in accordance with Material Safety Data Sheet (MSDS).

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

OXYGEN,
REFRIGERATED LIQUID

USP

UN 1073

CONTENTS: LITERS

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING:

DO NOT CHANGE OR FORCE FIT CONNECTIONS

EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE

VIGOROUSLY ACCELERATES COMBUSTION

NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container movement.
Container temperatures should not exceed 52 degrees C (125 degrees F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID:

IN CASE OF FROSTBITE, obtain medical treatment immediately.

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

OXYGEN, COMPRESSED USP

UN 1072



C.A.S. NO. 7782-44-7

Representative Labeling
pursuant to 21 CFR 207.3 (10)
Company name and contact information
are printed in this box

⚠ WARNING: HIGH PRESSURE, OXIDIZING GAS, VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT.

Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation.
Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

Use a back flow preventative device in the piping.

Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F).

Use in accordance with Material Safety Data Sheet (MSDS).

DO NOT REMOVE THIS PRODUCT LABEL.

⚠ WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size	Contents	Size	Contents
<input type="checkbox"/> "M6"	170 Liters	<input type="checkbox"/> "E"	682 Liters
<input type="checkbox"/> "C"	248 Liters	<input type="checkbox"/> "H"	6910 Liters
<input type="checkbox"/> "D"	415 Liters	<input type="checkbox"/> Other	____ Liters

03227002

LOT
LITER

164.

**Representative Labeling pursuant
to 21 CFR 207.3(10)**



**OXYGEN,
REFRIGERATED
LIQUID
USP**

UN 1073



CONTENTS: _____ **LITERS**

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

- △ WARNING:** DO NOT CHANGE OR FORCE FIT CONNECTIONS
EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER
PRESSURE
VIGOROUSLY ACCELERATES COMBUSTION.
NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY
EXPLODE ON IGNITION OR IMPACT.
CAN CAUSE SEVERE FROSTBITE.
Keep oil, grease, and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container movement.
Avoid spills. Do not walk on or roll equipment over spills.
Container temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with the Material Safety Data Sheet (MSDS).
- △ FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.
- △ WARNING:** For emergency use only when administered by properly trained
personnel for oxygen deficiency and resuscitation. For all other
medical applications, **Rx Only**.
Uninterrupted use of high concentrations of oxygen over a long
duration, without monitoring its effect on oxygen content of
arterial blood, may be harmful. Use only with pressure reducing
equipment and apparatus designed for oxygen. Do not attempt
to use on patients who have stopped breathing, unless used in
conjunction with resuscitative equipment.

Produced by Air Liquefaction

DO NOT REMOVE THIS PRODUCT LABEL.

Representative Labeling
pursuant to 21 CFR 207.3 (10)
Company name and contact information
are printed in this area

CAS NO: 7782-44-7

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:54593-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:54593-001-01	170 L in 1 CYLINDER		
2	NDC:54593-001-02	415 L in 1 CYLINDER		
3	NDC:54593-001-03	682 L in 1 CYLINDER		
4	NDC:54593-001-04	41 L in 1 DEWAR		
5	NDC:54593-001-05	46 L in 1 DEWAR		
6	NDC:54593-001-06	180 L in 1 DEWAR		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		04/10/2014	

Labeler - CHV Home Medical Equipment Company, LLC (940733558)

Registrant - CHV Home Medical Equipment Company, LLC (940733558)

Establishment

Name	Address	ID/FEI	Business Operations
CHV Home Medical Equipment Company, LLC		940733558	manufacture(54593-001)