## NITROGEN- nitrogen gas Alliance Welding Supplies, Inc.

-----

### Nitrogen

ALLIANCE Welding Supplies 1224 SIXTH St. . BERKELEY, CA 94710 88-414-6363 NITROGEN, COMPRESSED NF UN1066 DO NOT REMOVE THIS PRODUCT LABEL. NON-FLAMMABLE GAS 2 NITROGEN NF

Rx only. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9 Pressure PSIG at 70 degrees F Size Contents Liters



### REFRIGERATED LIQUID NITROGEN, REFRIGERATED LIQUID NF UN1977 NON-FLAMMABLE GAS 2

## Rx ONLY

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. DO NOT change or force fit connections. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7727-37-9

## CONTENTS: LTRS: CU. FT. DO NOT REMOVE THIS PRODUCT LABEL ALLIANCE Welding Supplies 1224 SIXTH St. . BERKELEY, CA 94710 88-414-6363



	oduct Informati	on						
Product Type PF			PRESCRIPTION ANIMAL DRUG		Item Code (Source)		NDC:50562-012	
Route of Administration			RESPIRATORY (INHALATION)					
Ac	tive Ingredient/	Active Moi	ety					
			ient Name		Basis of Strength		Strength	
Nitrogen (UNII: N762921K75) (Nitrogen -					Nitrogen		- 992 mL in 1 L	
Pa	ckaging							
#	Item Code	Pac	kage Description	Marketin	g Start Date	Mark	eting End Date	
1	NDC:50562-012-01	6216 L i	n 1 CYLINDER					
2	NDC:50562-012-02	8132 L i	n 1 CYLINDER					
3	NDC:50562-012-03	1456 L i	n 1 CYLINDER					
4	NDC:50562-012-04	3055 L i	n 1 CYLINDER					
5	NDC:50562-012-05	99434 L	in 1 CYLINDER					
6	NDC:50562-012-06	110606	L in 1 CYLINDER					
7	NDC:50562-012-07	147248	L in 1 CYLINDER					
8	NDC:50562-012-08	142378	L in 1 CYLINDER					
9	NDC:50562-012-09	134053	L in 1 CYLINDER					
10	NDC:50562-012-10	180057	L in 1 CYLINDER					
11	NDC:50562-012-11	163262	L in 1 CYLINDER					
	NDC:50562-012-12	153498	L in 1 CYLINDER					

# Labeler - Alliance Welding Supplies, Inc. (029292513)

Establishment									
Name	Address	ID/FEI	<b>Business Operations</b>						
Alliance Welding Supplies, Inc.		961655144	manufacture						

Revised: 12/2015

Alliance Welding Supplies, Inc.