

OXYGEN - oxygen gas
American Welding & Gas

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Liquid Oxygen Label

OXYGEN,
REFRIGERATED LIQUID
USP

UN1073

REFRIGERATED LIQUID
ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.
DO NOT CHANGE OR FORCE FIT CONNECTIONS.
CONTENTS: LTRS: ____, CU FT: ____

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.
Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.
VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52°C (125°F)

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

DO NOT REMOVE THIS PRODUCT LABEL.

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**



UN1073

1 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. 1
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS:

LTRS:

CU.FT.:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE

VIGOROUSLY ACCELERATES COMBUSTION
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin, or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drag. Use suitable hand truck for container movement.
Avoid spills. Do not walk on or roll equipment over spills.
Cylinder temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with the **Material Safety Data Sheet (MSDS)**.

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.
CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

inweld corp

Your Source for Welding Supplies and Inert Gases
5353 WEST SOUTHERN AVENUE
INDIANAPOLIS, IN 46241
(317) 248-0651

47136
18 1005

OXYGEN

oxygen gas

Product Information

| | | | |
|--------------------------------|--------------------------|---------------------------|---------------|
| Product Type | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:49778-002 |
| Route of Administration | RESPIRATORY (INHALATION) | | |

Active Ingredient/Active Moiety

| Ingredient Name | Basis of Strength | Strength |
|--|--------------------------|-----------------|
| Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065) | Oxygen | 992 L in 1000 L |

Packaging

| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
|----------|------------------|----------------------------|-----------------------------|---------------------------|
| 1 | NDC:49778-002-01 | 140 L in 1 DEWAR | | |

Marketing Information

| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
|---------------------------|---|-----------------------------|---------------------------|
| unapproved medical gas | | 05/01/2009 | |

Labeler - American Welding & Gas (035216530)

Establishment

| Name | Address | ID/FEI | Business Operations |
|------------------------|----------------|---------------|----------------------------|
| American Welding & Gas | | 832328061 | manufacture |

Revised: 2/2010

American Welding & Gas