

NITROUS OXIDE- nitrous oxide gas
AMERICAN WELDING & GAS, INC.

Nitrous Oxide

NITROUS OXIDE UN1070 NON-FLAMMABLE GAS 2 OXIDIZER 5.1 USP MEDICAL GAS
Size G M 20 LB. E Weight 55 LB. 25 LB. 20 LB. 6 LB. LITERS 13,539 6,769 4,835 1,451
Rx only. WARNING: Administration of Nitrous Oxide may be hazardous or
contraindicated. For use only by or under the supervision of a licensed practitioner who
is experienced in the use and administration of Nitrous Oxide and is familiar with the
indications, effects, dosages, methods, and frequency and duration of administration,
and with the hazards, contraindications and side effects, and the precautions to be
taken. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER CONTAINS GAS UNDER
PESSURE; MAY EXPLODE IF HEATED. MAY CUASE DROWSINESS OR DIZZINESS. MAY
DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. Do not
handle until all safety precautions have been read and understood. Keep and store away
from clothing and other combustible materials. Keep valves and fittings free from grease
and oil. Avoide breathing gas. Do not put in eyes on skin or on clothing. Use and store
only outdoors or in a well-ventilated place. In case of fire: stop leak if safe to do so. Use
a back flow preventive device in the piping. Use only with equipment of compatible
materials of construction and rated for cylinder pressure. Use only with equipment
cleaned for oxygen service. Open valve slowly. Close valve after each use and when
empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125
degrees F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF
INHALED: Remove person to fresh air and keep comfortable for breathing. Call a
POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Thaw frosted parts
with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
WARNING: This product contains a chemical known to the state of California to cause
birth defects or other reproductive harm.
CAS: 10024-97-2 DO NOT REMOVE THIS PRODUCT LABEL
SCOTT-GROSS COMPANY, INC. 664 MAGNOLIA AVENUE . LEXINGTON, KY 40505 1-800-
967-6874 . WWW.SCOTTGROSS.COM

NITROUS OXIDE

UN1070



| | Size | Weight | LITERS |
|--------------------------|--------|--------|--------|
| <input type="checkbox"/> | G | 55 LB. | 13.529 |
| <input type="checkbox"/> | M | 28 LB. | 6.769 |
| <input type="checkbox"/> | 20 LB. | 20 LB. | 4.835 |
| <input type="checkbox"/> | E | 6 LB. | 1.451 |
| <input type="checkbox"/> | | | |

For use only. WARNING: Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

CAS: 10024-97-2

DO NOT REMOVE THIS PRODUCT LABEL.



SCOTT-GROSS COMPANY, INC.
664 MAGNOLIA AVENUE • LEXINGTON, KY 40505
1-800-967-6874 • WWW.SCOTTGROSS.COM

SG-221 V004 (03/15)

NITROUS OXIDE

nitrous oxide gas

Product Information

| | | | | |
|--|---|--|-----------------------------|---------------------------|
| Product Type | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:52346-012 | |
| Route of Administration | RESPIRATORY (INHALATION) | | | |
| Active Ingredient/Active Moiety | | | | |
| Ingredient Name | | Basis of Strength | Strength | |
| NITROUS OXIDE (UNII: K50XQU1029) (NITROUS OXIDE - UNII:K50XQU1029) | | NITROUS OXIDE | 990 mL in 1 L | |
| Packaging | | | | |
| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
| 1 | NDC:52346-012-05 | 13539 L in 1 CYLINDER; Type 0: Not a Combination Product | 12/01/1974 | |
| 2 | NDC:52346-012-06 | 6769 L in 1 CYLINDER; Type 0: Not a Combination Product | 12/01/1974 | |
| 3 | NDC:52346-012-07 | 4835 L in 1 CYLINDER; Type 0: Not a Combination Product | 12/01/1974 | |
| 4 | NDC:52346-012-08 | 1451 L in 1 CYLINDER; Type 0: Not a Combination Product | 12/01/1974 | |
| Marketing Information | | | | |
| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date | |
| NDA | NDA206009 | 12/01/1974 | | |

Labeler - AMERICAN WELDING & GAS, INC. (868040283)

Establishment

| Name | Address | ID/FEI | Business Operations |
|------------------------------|---------|-----------|------------------------|
| AMERICAN WELDING & GAS, INC. | | 116724243 | manufacture(52346-012) |

Revised: 4/2021

AMERICAN WELDING & GAS, INC.