

OXYGEN- oxygen gas
Empresas De Soldaduras

Empresas de Soldaduras - Oxygen

Oxygen

OXYGEN, COMPRESSED USP UN 1072

OXYGEN 2 (R-K14) 115933

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS:

LTRS: ____

CU.FT. ____

EMPRESAS DE SOLDADURAS

986 Ave San Luis. • Arecibo, PR 00612

787.783.0262

OXYGEN,
COMPRESSED
USP

UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52° C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS:
LITR.
CU.FT.



EMPRESAS DE SOLDADURAS
986 Ave San Luis • Arecibo, PR 00612
787.783.0262

Oxygen

OXYGEN, COMPRESSED USP

UN 1072

OXYGEN 2 (R-K14) 133578R

EMPRESAS DE SOLDADURAS

986 Ave San Luis. • Arecibo, PR 00612

787.783.0262

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size	Contents	Size	Contents
<input type="checkbox"/> M6	170 Liters	<input type="checkbox"/> E	682 Liters
<input type="checkbox"/> C	248 Liters	<input type="checkbox"/> H	6910 Liters

D

415 Liters

 Other

____ Liters

**OXYGEN,
COMPRESSED
USP
UN1072**



C.A.S. NO. 7782-44-7

**EMPRESAS
DE SOLDADURAS**

986 Ave San Luis ■ Arecibo, PR 00612

787.783.0262



⚠ DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. **DO NOT REMOVE THIS PRODUCT LABEL.**

⚠ WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size	Contents	Size	Contents
<input type="checkbox"/> M6	470 Liters	<input type="checkbox"/> E	680 Liters

<input type="checkbox"/> MB	170 Liters	<input type="checkbox"/> E	682 Liters
<input type="checkbox"/> C	248 Liters	<input type="checkbox"/> H	6910 Liters
<input type="checkbox"/> D	415 Liters	<input type="checkbox"/> Other	_____ Liters

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:80421-100
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	1 L in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:80421-100-01	400 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2020	
2	NDC:80421-100-02	670 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2020	
3	NDC:80421-100-03	3570 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2020	
4	NDC:80421-100-04	7160 L in 1 TANK; Type 0: Not a Combination Product	07/01/2020	
5	NDC:80421-100-05	8580 L in 1 TANK; Type 0: Not a Combination Product	07/01/2020	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205849	07/01/2020	

Labeler - Empresas De Soldaduras (117611583)

Establishment

Name	Address	ID/FEI	Business Operations
Empresas De Soldaduras		117611583	manufacture(80421-100)