

NITROUS OXIDE- nitrous oxide gas
MITCHELL WELDING SUPPLY

Nitrous Oxide

NITROUS OXIDE USP

UN1070

Rx only. WARNING: Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. DANGER: MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. CAS: 10024-97-2



NITROUS OXIDE USP

UN1070

DO NOT REMOVE THIS LABEL.

Rx only. **WARNING:** Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. In case of fire: Stop leak if safe to do so. Store locked up. Dispose of contents/container in accordance with container supplier/owner instructions. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 10024-97-2

PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE.




Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. In case of fire: Stop leak if safe to do so. Store locked up. Dispose of contents/container in accordance with container supplier/owner instructions. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 10024-97-2 DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: This product can expose you to chemicals including Nitrous Oxide, which is know to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NITROUS OXIDE USP UN1070	 	MWS 3539 HIGHWAY 271 • TYLER, TX 75708 903-593-7343
CONTENTS:		CU FT <input type="checkbox"/> LITERS <input type="checkbox"/>
R Only.		
WARNING: Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.		
DANGER: MAY CAUSE OR INTENSIFY FIRE. OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE.		
Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. In case of fire: Stop leak if safe to do so. Store locked up. Dispose of contents/container in accordance with container supplier/owner instructions. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.		
FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.		
CAS: 10024-97-2	DO NOT REMOVE THIS PRODUCT LABEL.	
WARNING: This product can expose you to chemicals including Nitrous Oxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .		

NITROUS OXIDE

nitrous oxide gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:72276-002
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
NITROUS OXIDE (UNII: K50XQU1029) (NITROUS OXIDE - UNII:K50XQU1029)	NITROUS OXIDE	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:72276-002-01	29.03 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
2	NDC:72276-002-02	3.04 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
3	NDC:72276-002-03	185 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
4	NDC:72276-002-04	370 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
5	NDC:72276-002-05	940 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
6	NDC:72276-002-06	1225 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
7	NDC:72276-002-07	1590 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
8	NDC:72276-002-08	2466 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
9	NDC:72276-002-09	4930 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
10	NDC:72276-002-10	7570 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
11	NDC:72276-002-11	8524 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
12	NDC:72276-002-12	12300 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
13	NDC:72276-002-13	13800 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
14	NDC:72276-002-14	15800 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
15	NDC:72276-002-15	18578 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
16	NDC:72276-002-16	95155 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA209989	07/05/2018	

Labeler - MITCHELL WELDING SUPPLY (047833462)

Establishment

Name	Address	ID/FEI	Business Operations
MITCHELL WELDING SUPPLY		047833462	manufacture(72276-002)

Establishment

Name	Address	ID/FEI	Business Operations
MITCHELL WELDING SUPPLY		118920889	manufacture(72276-002)

Revised: 2/2023

MITCHELL WELDING SUPPLY