

OXYGEN- oxygen liquid
Weiler Welding Company

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, [click here](#).

OXYGEN, REFRIGERATED LIQUID

USP

[OXYGEN 2 SYMBOL]

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITIONCONTENTS:

LOT #: _____

WARNING:For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING:EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52 degrees C (125 degrees F)

Close valve after each use and when empty.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

[Weiler Welding Logo]

2400 SANDRIDGE DR. DAYTON, OHIO
8598 INDUSTRY PARK DR. PIQUA, OHIO
2865 SELLARS ROAD MORAINE, OHIO
5 EAST MAIN RICHMOND, INDIANA

EMERGENCY RESPONSE NUMBER: 1-800-424-9300

OXYGEN

oxygen liquid

Product Information

| | | | |
|--------------------------------|--------------------------|---------------------------|---------------|
| Product Type | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:48664-001 |
| Route of Administration | RESPIRATORY (INHALATION) | | |

Active Ingredient/Active Moiety

| Ingredient Name | Basis of Strength | Strength |
|--|--------------------------|----------------------|
| Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065) | Oxygen | 1.13835106 kg in 1 L |

Packaging

| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
|----------|------------------|---|-----------------------------|---------------------------|
| 1 | NDC:48664-001-02 | 1 in 1 CYLINDER | 01/01/1920 | |
| 1 | NDC:48664-001-01 | 154344 L in 1 CYLINDER; Type 0: Not a Combination Product | | |

Marketing Information

| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
|------------------------|--|----------------------|--------------------|
| unapproved medical gas | | 01/01/1920 | |

Labeler - Weiler Welding Company (004274403)

Registrant - Weiler Welding Company (004274403)

Establishment

| Name | Address | ID/FEI | Business Operations |
|------------------------|---------|-----------|------------------------|
| Weiler Welding Company | | 004274403 | manufacture(48664-001) |

Revised: 11/2016

Weiler Welding Company