

OXYGEN - oxygen gas
Wyandotte Welding Supply Inc.

Oxygen

OXYGEN, COMPRESSED USP

UN 1072

OXYGEN2

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7. RETURN WITH 25 PSIG. DO NOT REMOVE THIS PRODUCT LABEL.

LAB GASES DIVISION OF WYANDOTTE WELDING SUPPLY

2025 EUREKA AVENUE PO BOX 96

WYANDOTTE, MI 48192

(734) 282-3830 1-800-397-0669

FAX: (734) 282-6899

Lot #

Contents:



OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

CONTENTS:

LOT #:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produce by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

LAB GASES DIVISION OF WYANDOTTE WELDING SUPPLY

2025 EUREKA AVENUE PO BOX 96

WYANDOTTE, MN 48192

(734) 282-3830 1-800-397-0669

FAX: (734) 282-6899

OXYGEN, REFRIGERATED LIQUID

USP

UN1073

1 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. 1

CONTENTS: _____

LOT #: _____

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.
 Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquidefacto[®].

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.
 VIGOROUSLY ACCELERATES COMBUSTION.
 COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT
 CAN CAUSE SEVERE FROSTBITE.
 Keep oil, grease, and combustibles away.
 Use only with equipment cleaned for oxygen service.
 Store and use with adequate ventilation.
 Do not get liquid in eyes, on skin, or clothing.
 For liquid withdrawal, wear face shield and gloves.
 Do not drop. Use suitable hand truck for container movement.
 Avoid spills. Do not walk on or roll equipment over spills.
 Cylinder temperature should not exceed 52°C (125°F).
 Close valve after each use and when empty.
 Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.
 CAS: 7782-44-7
DO NOT REMOVE THIS PRODUCT LABEL.

LAB GASES DIVISION OF WYANDOTTE WELDING SUPPLY
 2025 EUREKA AVENUE • P.O. BOX 96 • WYANDOTTE, MI 48192
 (734) 282-3830 • 1-800-397-0669 • FAX: (734) 282-6899

47136
1000

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:63045-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:63045-001-01	420 L in 1 CYLINDER		
2	NDC:63045-001-02	690 L in 1 CYLINDER		
3	NDC:63045-001-03	3160 L in 1 CYLINDER		
4	NDC:63045-001-04	6900 L in 1 CYLINDER		
5	NDC:63045-001-05	248 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205827	05/16/2006	

Labeler - Wyandotte Welding Supply Inc. (017459025)

Establishment

Name	Address	ID/FEI	Business Operations
Wyandotte Welding Supply Inc.		017459025	manufacture(63045-001)

Revised: 5/2014

Wyandotte Welding Supply Inc.