


NITROGEN- nitrogen gas
Jackson Welding Supply Co Inc.

nitrogen

NITROGEN, COMPRESSED NF UN 1066 NON-FLAMMABLE GAS 2 Rx ONLY

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9 DO NOT REMOVE THIS PRODUCT LABEL. CONTENTS: LTRS: CU FT:
JACKSON WELDING & GAS PRODUCTS 4 PIXLEY INDUSTRIAL PKWY ROCHESTER, NY
14624 . 585-235-2920



NITROGEN, REFRIGERATED LIQUID NF UN1977 Contents: Lot Number: NON-FLAMMABLE GAS 2

Always keep container in upright position.

WARNING: Rx ONLY Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE. CAN CAUSE RAPID SUFFOCATION. CAN CAUSE SEVERE FROSTBITE. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Close valve after each use and when empty. Use in

accordance with the Material Safety Data Sheet (MSDS).

FIRST AID IF INHALED: Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. IN CASE OF FROSTBITE, obtain medical treatment immediately. PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION. DO NOT REMOVE THIS PRODUCT LABEL



NITROGEN

nitrogen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:42068-002
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
NITROGEN (UNII: N762921K75) (NITROGEN - UNII:N762921K75)	NITROGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42068-002-01	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
2	NDC:42068-002-02	8608 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205766	01/01/1973	

Labeler - Jackson Welding Supply Co Inc. (013113287)**Establishment**

Name	Address	ID/FEI	Business Operations
Jackson Welding Supply Co Inc.		013113287	manufacture(42068-002)

Revised: 10/2021

Jackson Welding Supply Co Inc.