

OXYGEN- oxygen gas
Liquid O2 Transfills, Inc.

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen

Principal for Oxygen Product

OXYGEN,

REFRIGERATED

LIQUID USP

UN 1073

CONTENTS _____ LITERS

CAS NO: 7782-44-7

DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS
KEEP CONTAINER IN UPRIGHT POSITION. DO NOT
CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY
FIRE; OXIDIZER, CONTAINS REFRIGERATED GAS: MAY CAUSE
CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH
LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free from grease and oil. In case of fire, stop leak if safe to do so. Avoid spills. Do not walk or roll equipment over spills. Store and use in a well ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52 F. Container temperature should not exceed 52 F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for

container movement.

FIRST AID:

IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water.

Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

**OXYGEN,
REFRIGERATED
LIQUID
USP**
UN 1073



CONTENTS: _____ LITERS

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

△WARNING: DO NOT CHANGE OR FORCE FIT CONNECTIONS
EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER
PRESSURE
VIGOROUSLY ACCELERATES COMBUSTION.
NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY
EXPLODE ON IGNITION OR IMPACT.
CAN CAUSE SEVERE FROSTBITE.
Keep oil, grease, and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves

For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container movement.
Avoid spills. Do not walk on or roll equipment over spills.
Container temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

△ **FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

△ **WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx Only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

DO NOT REMOVE THIS PRODUCT LABEL.

Representative Labeling
pursuant to 21 CFR 207.3 (10)
Company name and contact information
are printed in this area

CAS NO: 7782-44-7

OXYGEN

COMPRESSED

USP

UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °c (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency

and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen

content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**OXYGEN,
COMPRESSED USP
UN 1072**



DANGER:
MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ©Applied Home Healthcare Equipment 2014

Contents	Size
113 Liters	<input type="checkbox"/> M4
165 Liters	<input type="checkbox"/> M6
255 Liters	<input type="checkbox"/> C
425 Liters	<input type="checkbox"/> D
680 Liters	<input type="checkbox"/> E
7080 Liters	<input type="checkbox"/> H
____ Liters	<input type="checkbox"/> Other

**Representative Labeling
pursuant to 21 CFR 207.3 (10)
Company name and contact information
are printed in this box**

~~LOT~~
~~EXPIRATION DATE~~

Representative Labeling
pursuant to 21 CFR 207.3 (10)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:72712-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:72712-001-01	113 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
2	NDC:72712-001-02	165 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
3	NDC:72712-001-03	164 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
4	NDC:72712-001-04	198 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
5	NDC:72712-001-05	255 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
6	NDC:72712-001-06	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
7	NDC:72712-001-07	640 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
8	NDC:72712-001-08	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	

9	NDC:72712-001-09	1738 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
10	NDC:72712-001-10	3455 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
11	NDC:72712-001-11	7080 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
12	NDC:72712-001-12	46 L in 1 DEWAR; Type 0: Not a Combination Product	01/30/2002	
13	NDC:72712-001-13	41 L in 1 DEWAR; Type 0: Not a Combination Product	01/30/2002	
14	NDC:72712-001-14	180 L in 1 DEWAR; Type 0: Not a Combination Product	01/30/2002	
15	NDC:72712-001-15	230 L in 1 DEWAR; Type 0: Not a Combination Product	01/30/2002	
16	NDC:72712-001-16	3198 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	
17	NDC:72712-001-17	8688 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2002	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		01/30/2002	

Labeler - Liquid O2 Transfills, Inc. (102376253)

Establishment

Name	Address	ID/FEI	Business Operations
Liquid O2 Transfills, Inc.		102376253	manufacture(72712-001)

Establishment

Name	Address	ID/FEI	Business Operations
Liquid O2 Transfills, Inc.		117252066	manufacture(72712-001)

Revised: 3/2024

Liquid O2 Transfills, Inc.