

OXYGEN- oxygen gas
Rezk Medical Supply

Oxygen

OXYGEN COMPRESSED LABEL

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight and ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ©Applied Home Healthcare Equipment 2014

CAS NO: 7782-44-7

Contents	Size
113 Liters	__M4
165 Liters	__M6
255 Liters	__ C
425 Liters	__ D
680 Liters	__ E
7080 Liters	__ H
__ Liters	__ Other

REZK MEDICAL SUPPLY

FOR ALL YOUR HOME PATIENT NEEDS

115 South Main Street

Carrolltown, PA 15722

866-646-6818

OXYGEN, COMPRESSED USP

UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.



Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ©Applied Home Healthcare Equipment 2014

Contents	Size
113 Liters	<input type="checkbox"/> M4
165 Liters	<input type="checkbox"/> M6
255 Liters	<input type="checkbox"/> C
425 Liters	<input type="checkbox"/> D
680 Liters	<input type="checkbox"/> E
3198 Liters	<input type="checkbox"/> M
_____ Liters	<input type="checkbox"/> Other



115 South Main Street
Carrolltown, PA 15722
866-646-6818

OXYGEN REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP UN 1073 OXYGEN 2

CONTENTS: _____ LITERS

CAS NO: 7782-44-7

DANGER: REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free from grease and oil. In case of fire, stop leak if safe to do so. Avoid spills. Do not walk or roll equipment over spills. Store and use in a well ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Container temperature should not exceed 52°C/125°F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

FIRST AID:

IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

!ALWAYS KEEP CONTAINER IN UPRIGHT POSITION!

Rezk Medical Supply

115 South Main Street

Carrolltown, PA 15722

1-866-646-6818



CONTENTS: _____ **LITERS**

CAS NO: 7782-44-7

2



DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free from grease and oil. In case of fire, stop leak if safe to do so. Avoid spills. Do not walk or roll equipment over spills. Store and use in a well ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52 °C/125 °F. Container temperature should not exceed 52 °C/125 °F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

FIRST AID:

IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure

reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

Rezk Medical Supply

115 South Main Street
Carrolltown, PA 15722
1-866-646-6818

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:52751-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:52751-001-01	113 L in 1 CYLINDER; Type 0: Not a Combination Product	08/01/2010	
2	NDC:52751-001-02	170 L in 1 CYLINDER; Type 0: Not a Combination Product	08/01/2010	
3	NDC:52751-001-03	248 L in 1 CYLINDER; Type 0: Not a Combination Product	08/01/2010	
4	NDC:52751-001-04	426 L in 1 CYLINDER; Type 0: Not a Combination Product	08/01/2010	
5	NDC:52751-001-05	671 L in 1 CYLINDER; Type 0: Not a Combination Product	08/01/2010	
6	NDC:52751-001-06	3462 L in 1 CYLINDER; Type 0: Not a Combination Product	08/01/2010	
7	NDC:52751-001-07	21 L in 1 DEWAR; Type 0: Not a Combination Product	08/01/2010	
8	NDC:52751-001-08	31 L in 1 DEWAR; Type 0: Not a Combination Product	08/01/2010	
9	NDC:52751-001-09	36 L in 1 DEWAR; Type 0: Not a Combination Product	08/01/2010	
10	NDC:52751-001-10	46 L in 1 DEWAR; Type 0: Not a Combination Product	08/01/2010	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1998	

Labeler - Rezk Medical Supply (808613439)

Registrant - Rezk Medical Supply (808613439)

Establishment

Name	Address	ID/FEI	Business Operations
Rezk Medical Supply		603592838	manufacture(52751-001)

Revised: 10/2019

Rezk Medical Supply