

OXYGEN- oxygen gas
Albright Welding Supply Co., Inc.

Oxygen

OXYGEN, COMPRESSED USP
US1072
PRODUCED BY AIR LIQUEFACTION
OXYGEN 2
OXYGEN USP

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7. **DO NOT REMOVE THIS PRODUCT LABEL.**

Contents: LTRS CU. FT.
ALBRIGHT WELDING SUPPLY CO. INC.
3132 EAST LINCOLN WAY
WOOSTER, OH 44691
330-264-2021



OXYGEN, REFRIGERATED LIQUID USP

UN1073

OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children.

Federal law requires that this container be refilled with oxygen USP only be establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSITY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

SECURE ALL CYLINDERS WHILE IN STORAGE AND IN USE. DO NOT REMOVE THIS PRODUCT LABEL.

ALBRIGHT WELDING SUPPLY CO. INC.

3132 EAST LINCOLN WAY

WOOSTER, OH 44691

330-264-2021

OXYGEN, REFRIGERATED LIQUID USP UN1073

WARNING

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.
Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children.
Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.
PRODUCED BY AIR LIQUEFACTION

DANGER

- MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
 - CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.
 - COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.
- Do not handle until all safety precautions have been read and understood.
Keep and store away from clothing and other combustible materials.
Keep valves and fittings free from grease and oil.
Use and store only outdoors or in a well-ventilated place.
Wear cold insulating gloves, face shield, and eye protection.
In case of fire: Stop leak if safe to do so.
Use a back flow preventive device in the piping.



FIRST AID

Use only with equipment of compatible materials of construction and rated for cylinder pressure.
Use only with equipment cleaned for oxygen service.
DO NOT change or force fit connections.
Avoid spills. Do not walk on or roll equipment over spills.
Close valve after each use and when empty.
Always keep container in upright position.
Read and follow the Safety Data Sheet (SDS) before use.

- IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

ALBRIGHT WELDING SUPPLY CO. INC.
3132 EAST LINCOLN WAY
WOOSTER, OH 44691 • 330-264-2021

LABEL SOLUTIONS, INC. • 1-800-289-8200 • 8035 09/10

**SECURE ALL CYLINDERS WHILE IN STORAGE AND IN USE.
DO NOT REMOVE THIS PRODUCT LABEL.**



OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:52272-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:52272-001-01	425 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	
2	NDC:52272-001-02	560 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	01/11/2024
3	NDC:52272-001-03	700 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	
4	NDC:52272-001-04	1550 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	01/11/2024
5	NDC:52272-001-05	2600 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	01/11/2024

6	NDC:52272-001-06	3550 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	
7	NDC:52272-001-07	4000 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	01/11/2024
8	NDC:52272-001-08	7100 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	01/11/2024
9	NDC:52272-001-09	8000 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	
10	NDC:52272-001-10	9500 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	
11	NDC:52272-001-13	198 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	01/11/2024
12	NDC:52272-001-14	1942 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	
13	NDC:52272-001-15	212 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	
14	NDC:52272-001-16	150 L in 1 CYLINDER; Type 0: Not a Combination Product	08/27/1983	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205849	08/27/1983	

Labeler - Albright Welding Supply Co., Inc. (004454443)

Establishment

Name	Address	ID/FEI	Business Operations
Albright Welding Supply Co., Inc.		004454443	manufacture(52272-001)

Revised: 1/2024

Albright Welding Supply Co., Inc.