

**OXYGEN- oxygen gas**  
**Hagan, Logan Welding Supply Inc**

-----  
**oxygen**

OXYGEN, COMPRESSED LIQUID USP UN1072 DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN 2 815033 (08/04)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

CAUTION: Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.


WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep

oil, grease away. Open valve slowly. Store and use with adequate ventilation.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52C (125F). Use in accordance with the Material Safety Data Sheets (MSDS). CAS: 7782-44

-7

DO NOT REMOVE THIS PRODUCT LABEL  
LOGAN HAGAN WELDING SUPPLY INC.  
303 N Zetterower Ave. Statesboro, GA 30459



912-764-6481

OXYGEN, COMPRESSED LIQUID USP UN1072 DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN 2 815033 (08/04)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

CAUTION: Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep

oil, grease away. Open valve slowly. Store and use with adequate ventilation.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52C (125F). Use in accordance with the Material Safety Data Sheets (MSDS). CAS: 7782-44

-7

DO NOT REMOVE THIS PRODUCT LABEL  
 LOGAN HAGAN WELDING SUPPLY INC.  
 303 N Zetterower Ave. Statesboro, GA 30459



912-764-6481

<b>OXYGEN</b>			
oxygen gas			
<b>Product Information</b>			
<b>Product Type</b>	PRESCRIPTION ANIMAL DRUG	<b>Item Code (Source)</b>	NDC:49507-011
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		
<b>Active Ingredient/Active Moiety</b>			
	<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
	Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

**Packaging**

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:49507-011-01	170 L in 1 CYLINDER		
2	NDC:49507-011-02	380 L in 1 CYLINDER		
3	NDC:49507-011-03	662 L in 1 CYLINDER		
4	NDC:49507-011-04	3454 L in 1 CYLINDER		
5	NDC:49507-011-05	6909 L in 1 CYLINDER		
6	NDC:49507-011-06	30 L in 1 DEWAR		
7	NDC:49507-011-07	45 L in 1 DEWAR		

**Marketing Information**

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141413	01/01/1977	

**Labeler** - Hagan, Logan Welding Supply Inc (033847066)

**Establishment**

Name	Address	ID/FEI	Business Operations
Hagan, Logan Welding Supply Inc		033874066	manufacture

Revised: 7/2020

Hagan, Logan Welding Supply Inc